



### SPECIAL FEATURES

- ❖ 80 PLUS® Bronze Certified High Efficiency
- ❖ Highly Reliable 105 °C Japanese Brand Capacitor
- ❖ Ample +12 V Outputs
- ❖ Active Power Factor Correction (99 % PF Typical)
- ❖ Double Forward Converter Design
- ❖ Smart & Silent Fan Control (S²FC)
- ❖ 120 mm Fluid Dynamic Bearing (FDB) Fans
- ❖ Soft-Mount Rubber Cushions
- ❖ Patented Easy Swap Connector
- ❖ Universal AC Input (Full Range)
- ❖ Ultra Ventilation (Honeycomb Structure)
- ❖ 5 Years Warranty




### POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
<b>S12II - 620 Bronze</b>	24 A	24 A	48 A	0.8 A	2.5 A	620 W
	130 W		576 W	9.6 W	12.5 W	
<b>S12II - 520 Bronze</b>	24 A	24 A	40 A	0.8 A	2.5 A	520 W
	130 W		480 W	9.6 W	12.5 W	
<b>S12II - 430 Bronze</b>	20 A	20 A	30 A	0.8 A	2.5 A	430 W
	130 W		360 W	9.6 W	12.5 W	

### WIRE CONFIGURATION

Cable						
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)
<b>S12II - 620 Bronze</b>	1	1	2	8	4	1
<b>S12II - 520 Bronze</b>	1	1	2	6	4	1
<b>S12II - 430 Bronze</b>	1	1	2	6	3	1



Safety & EMI / EMC Protection Features: OPP, OVP, SCP, UVP

Dimensions: L 150 x W 140 x H 86 mm



Specifications may change without prior notice



**Headquarters** Tel: +886-2-2659-0338 | Fax: +886-2-2659-0530 | sales@seasonic.com | www.seasonic.com  
**USA** Tel: +1 626-969-9966 | Fax: +1 626-969-9986 | ssa.sales@seasonic.com  
**Europe** sse.sales@seasonic.com  
**Japan** Tel: +81-3-6805-4085 | ssj.sales@seasonic.com