


Delock PCI Express x4 Card > 2 x external USB 3.1 Gen 2 Type-A female

Description

This PCI Express card by Delock expands the PC by two external USB 3.1 ports. Different USB Type-A devices, such as docking stations, card readers, external housings etc., can be connected to the card.



Specification

- Connector:
 - external:
 - 2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
 - internal:
 - 1 x SATA 15 pin power connector
 - 1 x PCI Express x4, V2.0
- Chipset: Asmedia ASM1142
- Data transfer rate up to:
 - SuperSpeed USB 10 Gbps,
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- Power supply via PCI Express interface or via SATA 15 pin power connector
- Electrical power per port: max. 4.5 watt (5 V / 900 mA)
- Supports eXtensible Host Controller Interface (xHCI) specifications 1.1
- Supports UASP

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content

- PCI Express card SuperSpeed USB 10 Gbps
- Low profile bracket
- Driver CD
- User manual

Item No. 89554

EAN: 4043619895540

Country of origin: China

Package: Retail Box



Images



General

Supported operating system:	Linux ex Kernel 4.6
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit

Interface

External:	2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
Internal:	1 x PCI Express x4, V2.0
	1 x SATA 15 pin male

Technical characteristics

Chipset:	Asmedia ASM1142
Data transfer rate:	USB 3.1 Gen 2 up to 10 Gb/s