

Delock USB Type-C™ 3.1 Docking Station 4K 30 Hz

Description

This docking station by Delock can be connected to a computer with a USB-C™ Alt-Mode or Thunderbolt™ 3 port and provides a variety of interfaces. Two monitors can be operated simultaneously at the mini DisplayPort and HDMI outputs, alternatively a single monitor at the VGA output. Three built-in USB Type-A ports allow the use of peripherals, and connections for a headset and gigabit network, as well as an SD / micro SD card reader, complete the features. With a USB-C™ power supply, laptops such as the Macbook or Chromebook can be charged during operation.



Note

The product is a Multi-Stream-Transport (MST) hub and supports the extended desktop configuration of Displayport 1.2. When Mac OS is used, the same image is displayed on both ports (mirrored), it is not possible to use both ports independently of each other.

Specification

- Connectors:
 - front side:
 - 1 x Gigabit LAN 10/100/1000 Mb/s RJ45 female
 - 1 x mini DisplayPort 20 pin female
 - 1 x HDMI-A 19 pin female
 - 1 x VGA 15 pin female
 - 1 x USB Type-C™ female (power supply)
 - back side:
 - 3 x USB 3.0 Type-A female
 - 1 x Headset 3.5 mm 4 pin jack
 - 1 x SD / SDHC / SDXC / MMC slot
 - 1 x Micro SD / SDHC / SDXC slot
 - 1 x USB Type-C™ male
- HDMI and DisplayPort ports support: extended and mirror, resolution up to 2560 x 1440 @ 60 Hz or 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- VGA resolution up to 1920 x 1080 @ 60 Hz
- Transfer of audio and video signals
- Output power: max. 10 W total,
 - 1 x USB Type-A female max. 7.5 W,
 - 2 x USB Type-A female max. 5 W (combined)
- Input power: 1 x USB Type-C™ female max. 60 W
- Metal housing
- Rubber pads for safe grip and secure stand
- Cable length incl. connector: ca. 18 cm
- Colour: silver-grey
- Dimensions (LxWxH): ca. 13.7 x 7.5 x 1.7 cm

System requirements

- Windows 8.1/8.1-64/10/10-64, Windows 10 Mobile, Android ex 6.0, Mac OS ex 10.9
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port

Package content

- USB-C™ docking station
- User manual

Item no. 87298


EAN: 4043619872985

Country of origin: China

Package: Retail Box



Images



General

Specification: SuperSpeed USB (USB 3.1 Gen 1)
 DisplayPort 1.2
 High Speed HDMI with Ethernet
 HDCP 1.4

Supported operating system: Android ex 6.0
 Windows 8.1 32-bit
 Windows 8.1 64-bit
 Windows 10 32-bit
 Windows 10 64-bit
 ex Mac OS 10.9

Interface

Output: 1 x RJ45 jack
 1 x mini DisplayPort 20 pin female
 1 x 3.5 mm 4 pin stereo jack female
 3 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
 1 x HDMI-A 19 pin female
 1 x VGA 15 pin female
 1 x SD slot
 1 x Micro SD slot

Input: 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male
 1 x USB Type-C™ female (power supply)

Technical characteristics

Maximum screen resolution: 3840 x 2160 @ 30 Hz

Signal transmission: video
 audio

Voltage: USB bus powered
 1 x USB Type-C™ Power Delivery female (optional for power supply)

Physical characteristics

Cable length incl. connector: 18 cm

Colour: silver