



USB 3.0 Type C HDMI Multiport Adaptor



User Manual DA-70847

1.0 INTRODUCTION

This is a USB-C to 2 USB 3.0 with Gigabit Ethernet and HDMI Hub. The two USB 3.0 ports allow you to connect 2 USB devices to the host computer or another hub. The host computer can easily get access to the network through the Gigabit Ethernet port and the HDMI port allows you to connect an extra monitor, so you can watch videos or slideshows on the big screen. It can work on Apple new Macbook Pro or Google new Chromebook Pixel and other USB-C supported devices.

2.0 FEATURES

- Support USB-C input and HDMI, RJ45, USB 3.0 output
- Support USB 3.0 super speed (5Gbps) transmission, downward compatible with USB 2.0
- Support 10/100/1000Mbps bandwidth
- Max 900mA per USB port when one port is connected
- USB 3.0 port supports to charge and transmit data for the USB device simultaneously
- Support HDMI resolution up to 4Kx2K@30Hz, 9Gbps bandwidth
- Multiple USB-C interfaces support plug and play, hot swap
- Easy to use and carry

3.0 SPECIFICATIONS

| Input/Output Connector | |
|-------------------------------|--|
| Input | USB-C Male x1 |
| Output | HDMI Female x1 USB 3.0 Female x2 RJ45 x1 |
| Resolutions | |
| Resolutions | Up to 4Kx2K@30Hz |
| Operating Frequency | |
| Vertical Frequency Range | 5Gbps transmission data |
| Physical | |
| Weight | 44.9g |
| Size (L-W-H) | 95x41x17 (mm) |
| Environmental | |
| Operating Temperature | 0°C to +45°C |
| Operating Humidity | 10% to 85% RH (no condensation) |
| Storage Temperature | -10°C to +70°C |
| Storage Humidity | 5% to 90% RH (no condensation) |
| Power Supply | |
| USB 3.0 Port | Max 900mA per port |
| Regulatory Approvals | |
| Certifications | FCC, CE |

4.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

5.0 OPERATION

1. Connect the USB-C male port of this product to computer
2. Connect HDMI output of this product to HDTV with one HDMI cable
3. Connect the USB 3.0 output of this product to USB 3.0 devices with a USB 3.0 cable
4. Connect Gigabit Ethernet port of this product to Ethernet Router with an Ethernet cable
5. Automatically or manually set IP address of computer

6.0 CONNECTION DIAGRAM



Hereby ASSMANN Electronic GmbH, declares that this device is in compliance with the requirements of Directive 2014/30/EU and the Directive 2011/65/EU for RoHS compliance. The complete declaration of conformity can be requested by post under the below mentioned manufacturer address.

Warning:

This device is a class B product. This equipment may cause some radio interference in living environment. In this case, the user can be requested to undertake appropriate measures to prevent interference.

www.assmann.com

Assmann Electronic GmbH
Auf dem Schüffel 3
58513 Lüdenscheid
Germany

