



# ICY BOX IB-HUB1477-C31

## Industrial 4 Port USB 3.1 (Gen 2) Type-C™ hub

### Key features

- Robust steel enclosure, industry level
- 2x USB 3.0 Type-A connectors for devices
- 2x USB 3.0 Type-C™ connectors for devices
- 1x USB 3.1 (Gen 2) Type-C™ to Type-C™ connector to PC
- USB 3.1 (Gen 2) Type-C™ transfer rate up to 10 Gbit/s
- 15 KV ESD surge protection
- Integrated brackets for mounting
- Can be mounted by screws on different surfaces



### Packing content

IB-HUB1477-C31, wall power supply, USB 3.1 (Gen 2) cable (60 cm), quick installation guide

## Made to last

The IB-HUB1477-C31 is made with a solid metal housing including screw holes for flexible utility in many industry areas, even if the environment is a bit rougher. The USB hub expands one USB 3.1 (Gen 2) port into additional four ports - twice USB Type-C™ and twice USB Type-A. Thanks to the transfer rates of up to 10 Gbit / second, this USB hub can be used in many situations. USB 3.1 (Gen 2) is downwards compatible therefore even older USB 3.0 and USB 2.0 devices can be used (but in the according transfer rates).

### Technical data

<b>Model</b>	IB-HUB1477-C31
<b>Article no.</b>	60560
<b>EAN code</b>	4250078169277
<b>Brand</b>	ICY BOX
<b>Colour</b>	Black
<b>Material</b>	Metal
<b>Interface to host computer</b>	USB 3.1 (Gen 2) Type-C™
<b>Interface</b>	2x USB 3.1 (Gen 2) Type-A 2x USB 3.1 (Gen 2) Type-C™

<b>Transfer rate</b>	Up to 10 Gbit/s
<b>UASP support</b>	Yes
<b>Plug &amp; Play</b>	Yes
<b>LED</b>	Power and access
<b>Power supply</b>	5 V / 4 A
<b>DC-Plug dimensions</b>	DC-plug: 10.79 x 5.46 x 2.03 mm
<b>Operating system</b>	Windows®, macOS®



## ICY BOX **IB-HUB1477-C31** Industrial 4 Port USB 3.1 (Gen 2) Type-C™ hub



### Robust and reliable?

This particularly sturdy 4-Port USB 3.1 (Gen 2) hub is made of steel and has integrated screw holes for mounting that make it perfect for a consistent and reliable use.



### All inclusive

The IB-HUB1477-C31 does not only have two super-speed USB Type-A connectors, but also two super-speed USB Type-C™ connectors, that means more USB Type-C™ devices can be connected even when the hub is in use.



### Control center

The USB 3.1 (Gen 2) ports offer the high data transfer rate with up to 10 Gbit/s. The hub is supplied with an AC power supply and at each port a LED signals USB connection and a separate LED shows that the power is connected.

#### Logistical data

**Packing unit:** 10 pcs/carton  
**Total weight:** 7.12 kg/carton  
**Gross weight (with packing):** 0.630 kg  
**Net weight:** 0.225 kg

**Dimension/carton:** 430x255x360 mm  
**Dimension (with packing):** 200x235x64 mm  
**Dimension of article:** 64x135x24 mm  
**Country of origin:** Taiwan