



Mini DisplayPort 1.2 to Multi-AV Active Converter

No.: 38311

Connects a Mini DisplayPort source to an HDMI, DisplayPort, DVI or VGA display

Description

- Converts a DisplayPort signal to HDMI, DP, DVI or VGA
- Supports HDMI and DP resolutions up to 4K@60Hz, VGA up to Full HD and DVI up to and above Full HD
- Easily connect with a single legacy or modern display at any one time
- Compact, portable design
- 2 year warranty

The Lindy Mini DisplayPort to Multi-AV Converter allows users to connect either a HDMI, DP, DVI or VGA screen to a Mini Displayport source. Supporting full 4K Ultra HD resolutions up to 3840x2160@60Hz on DP and HDMI displays, content can be viewed with superior clarity and stunning accuracy. DVI monitors are supported with a maximum resolution of 1920x1200@60Hz, VGA monitors and projectors up to 1920x1080@60Hz.

With its lightweight, low profile design, this converter easily fits into a notebook bag and simply expands available connectivity options, so users can connect to various digital and analogue video devices, without having to carry multiple adapters - ideal for BYOD applications.

Please note that the DVI port only provides digital, no analog signals

Technical details

Specifications

- AV Interface: Mini DisplayPort to DP, HDMI, DVI, VGA
- Interface Standard: DisplayPort 1.2, HDMI 2.0, DVI-I, VGA
- Supported Bandwidth: 21.6Gbps
- Maximum Input Resolution: 3840x2160@60Hz 4:4:4 8bit
- Maximum Output Resolution:
 - 3840x2160@60Hz 4:4:4 8bit (DP)
 - 3840x2160@60Hz RGB 8bit (HDMI)
 - 1920x1200@60Hz (DVI)
 - 1920x1200@60Hz (VGA)
- Chipset: PS8339B, ANX9833, PS8348B, PS176
- HDCP Support: HDCP 2.2

- Supported Audio: Pass-through for DP & HDMI
- Separate Audio Ports: -
- Special Features: -

Connectors

- Input: Mini DisplayPort (Male)
- Output:
 - HDMI Type A Female
 - DisplayPort Female
 - DVI-I Female
 - VGA Female

Physical Properties

- Dimensions (approx.) WxDxH:
 - Connector: 19x11x9mm (0.75x0.43x0.35in)
 - Housing: 106x46x14.5mm (4.17x1.81x0.57in)
- Cable Length: 150mm (5.91in)
- Housing Material: Plastic
- Jacket Material: PVC
- Jacket Diameter: 4.8mm (0.19in)
- Minimum Bend Radius: 48mm (1.89in)
- Net Weight: 0.053kg (0.12lb)
- Operating Temperature: 0° to 40° (32°F - 104°F)
- Storage Temperature: -10° to +70° (14°F - 158°F)
- Humidity: 10 - 85% RH (non-condensing)
- Colour: White

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 160x160x20mm (6.3x6.3x0.79in)
- Gross Weight: 0.089kg (0.2lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, Calif. Prop. 65

Package Contents

- Mini DisplayPort 1.2 to Multi-AV Active Converter

Purchasing Information

- No.: 38311
- EAN: 4002888383110