TP-Link TL-WR840N draadloze router Fast Ethernet Single-band (2.4 GHz) Grijs, Wit

Merk : TP-Link

Artikelcode: TL-WR840N

Productnaam : TL-WR840N

TP-Link TL-WR840N. Type WAN-aansluiting: RJ-45. Wifi-band: Single-band (2.4 GHz), Wifi-standaard: Wi-Fi 4 (802.11n), WLAN gegevensoverdrachtsnelheid (max): 300 Mbit/s. Interfacetype Ethernet LAN: Fast Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100 Mbit/s, Bekabelingstechnologie: 10/100Base-T(X). Ondersteunde beveiligingsalgoritmen: WEP, WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, Firewall: SPI. Ondersteunde netwerkprotocollen: IPv4, IPv6

WAN connection

Ethernet WAN *	✔
DSL WAN *	✘
SIM card slot *	✘
3G/4G USB modem compatibility *	✘
WAN connection type	RJ-45

Wireless LAN features

Wi-Fi band *	Single-band (2.4 GHz)
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)
WLAN data transfer rate (max) *	300 Mbit/s
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)

Network

Ethernet LAN *	✔
Ethernet LAN interface type *	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Cabling technology	10/100Base-T(X)
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3u
Port forwarding	✔
Port triggering	✔
Number of guest networks (2.4 GHz)	1
VPN support	PPTP, L2TP, IPSec
Receiver sensitivity	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER

Protocols

Supported network protocols	IPv4, IPv6

Design

Product colour	Grey, White
LED indicators	✔
On/off switch	✔
Product type *	Tabletop router

Certificates

Compliance certificates	RoHS, Federal Communications Commission (FCC), CE

Packaging content

Cables included	LAN (RJ-45)
AC adapter included	✔
Quick installation guide	✔

Sustainability

Sustainability compliance	✔

Antenna

Antenna design *	External
Antenna gain level (max)	5 dBi
Antennas quantity	2

Features

Built-in processor	✔
Processor cores	1

Power

Power source type *	DC
Output voltage	9 V

Ports & interfaces	
Ethernet LAN (RJ-45) ports *	4
USB port *	✘
DC-in jack	✔

Management features	
Web-based management	✔
Quality of Service (QoS) support	✔
Reset button	✔
WPS push button	✔

Security	
Security algorithms	WEP, WPA, WPA-Enterprise, WPA2, WPA2-Enterprise
Firewall	✔
Firewall security	SPI
Guest access	✔
Filtering	✔
MAC address filtering	✔
URL filtering	✔
DMZ support	✔

Protocols	
DHCP client	✔
DHCP server	✔
Universal Plug and Play (UPnP)	✔

Power	
Output current	0.6 A

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

System requirements	
Windows operating systems supported	Windows 2000, Windows 2000 Professional, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Linux operating systems supported	✔
Mac operating systems supported	✔

Weight & dimensions	
Width	182 mm
Depth	128 mm
Height	35 mm

Packaging data	
Package width	265 mm
Package depth	180 mm
Package height	86 mm
Package weight	430 g

Other features	
WLAN data transfer rates supported	11,54,300 Mbit/s

0115971613347

115971613347

6935364070533