



Delock USB 2.0 to 4 x serial adapter

Description

This USB 2.0 to serial adapter enables you to connect up to four different serial devices to a free USB port.



Specification

- Connector:
- 1 x USB 2.0 Type-B female >
- 4 x serial RS-232 DB9 male
- · Chipset: Moschip
- · Serial connector with screw nuts
- Data transfer rate up to 921.6 Kb/s
- · LED indicator
- Automatic IRQ and I/O address selection
- Four 16C450 / 16C550 compatible UARTs
- Supports FIFO 512 bytes per port (transmit / receive)

System requirements

- Windows 2000/XP/Server-2003/Vista/Vista-64/7/7-64/8/8-64/8.1/8.1-64/10/10-64
- · PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 4 x serial adapter
- USB 2.0 cable
- Driver CD
- User manual

Images





Item no. 87414

EAN: 4043619874149

Country of origin: China

Package: Retail Box







Function: Plug & Play Specification: RS-232 USB 1.1 USB 2.0 Supported operating system: Windows 7 32-bit Windows 8.1 64-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit LED indicator: Power Interface Power Connector 1: 1 x USB 2.0 Type-B Connector 2: 1 x Serial RS-232 DB9 male Technical characteristics Technical characteristics Chipset: A SIX/Moschip MCS 7840 Data transfer rate: 4 x up to 921,6 Kbps FIFO: 512 byte Data transmission: asynchronous full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing material: Housing material: Plastic Cable colour: USB AWM Style 2725 Cable colour: USB AWM Style 2725 Cable colour: Use AWM Style 2725 Cable length incl. connector: 1 m Pin finishing: gold-plate	General	
USB 1.1	Function:	Plug & Play
USB 2.0	Specification:	RS-232
Supported operating system: Windows 7 32-bit Windows 8.1 32-bit Windows 8.1 32-bit Windows 10 32-bit Windows 10 64-bit Windows 10 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-B Connector 2: 1 x Serial RS-232 DB9 male Technical characteristics Chipset: ASIX/Moschip MCS 7840 Data transfer rate: 4 x up to 921,6 Kbps FIFO: 512 byte Data transmission: asynchronous full duplex Current consumption: UART: USB to serial UART Physical characteristics Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG abta line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm		USB 1.1
Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 64-bit		USB 2.0
Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 64-bit	Supported operating system:	Windows 7 32-bit
Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit		Windows 7 64-bit
Windows 10 32-bit Windows 10 64-bit		Windows 8.1 32-bit
Windows 10 64-bit LED indicator: Power Interface Connector 1:		Windows 8.1 64-bit
Interface		Windows 10 32-bit
Treefrace Connector 1:		Windows 10 64-bit
Connector 1: 1 x USB 2.0 Type-B Connector 2: 1 x Serial RS-232 DB9 male Technical characteristics Chipset: ASIX/Moschip MCS 7840 Data transfer rate: 4 x up to 921,6 Kbps FIFO: 512 byte Data transmission: asynchronous full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	LED indicator:	Power
Connector 2: 1 x Serial RS-232 DB9 male Technical characteristics Chipset: ASIX/Moschip MCS 7840 Data transfer rate: 4 x up to 921,6 Kbps FIFO: 512 byte Data transmission: asynchronous full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Interface	
Technical characteristics Chipset: ASIX/Moschip MCS 7840 Data transfer rate: 4 x up to 921,6 Kbps FIFO: 512 byte Data transmission: asynchronous full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Connector 1:	1 x USB 2.0 Type-B
Chipset: ASIX/Moschip MCS 7840 Data transfer rate: 4 x up to 921,6 Kbps FIFO: 512 byte Data transmission: asynchronous full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Connector 2:	1 x Serial RS-232 DB9 male
Data transfer rate: 4 x up to 921,6 Kbps FIFO: 512 byte Data transmission: asynchronous full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Technical characteristics	
FIFO: 512 byte Data transmission: asynchronous full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Chipset:	ASIX/Moschip MCS 7840
Data transmission: asynchronous full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: Length: 95 mm Width: 60 mm	Data transfer rate:	4 x up to 921,6 Kbps
full duplex Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	FIFO:	512 byte
Current consumption: 50 mA UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Data transmission:	asynchronous
UART: USB to serial UART Physical characteristics Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm		full duplex
Housing colour: silver Housing material: Plastic Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Current consumption:	50 mA
Housing colour: Housing material: Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: Width: 60 mm	UART:	USB to serial UART
Housing material: Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Physical characteristics	
Cable type: USB AWM Style 2725 Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Housing colour:	silver
Cable colour: black Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Housing material:	Plastic
Cable length incl. connector: 1 m Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Cable type:	USB AWM Style 2725
Pin finishing: gold-plated Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Cable colour:	black
Conductor gauge: 28 AWG data line 24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Cable length incl. connector:	1 m
24 AWG power line Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Pin finishing:	gold-plated
Screw type: #4-40 UNC Length: 95 mm Width: 60 mm	Conductor gauge:	
Length: 95 mm Width: 60 mm		24 AWG power line
Width: 60 mm	Screw type:	
	-	
Height: 20 mm		
	Height:	20 mm