3M[™] Digital Projector X20



Need the brightness and clarity of a True XGA (1024 x 768) LCD projector in a lightweight model that you can take on-the-go? The 3M Digital Projector X20 may be just the right mobile solution you've been seeking. Weighing less than 4 lbs., this 2000 lumen*, 4:3 aspect ratio projector delivers a crisp image from 30-300 inches – perfect for almost any office, classroom or small space screen. Easily connect your PC to one of the RGB inputs or go even lighter with a PC-less .jpg presentation using the featured USB port. You can even personalize your settings and increase your security with the many 3M X20 features. It's lighter and brighter at it's best.





Connections

Computer:	RGB (x2 input)
USB:	USB for remote control mouse USB for PC-Less presentations
Video:	S-Video Video Composite
Audio:	Audio In: 3.5 mini jack (x1) Audio Out: 3.5 mini jack (x1)

Digital Projector X20: 78-9236-6922-6

1-800-328-1371 www.3m.com/meetings

Features

- Picture Freeze, Blank and Magnify (4x)
- Security: PIN Code Lock, My Screen Lock, Transition Detector, Kensington Lock Bar
- Adjustable Picture Mode: Normal, Cinema, Dynamic, Whiteboard, Blackboard
- Custom personalization with *My Screen, My Button, My Memory* features

Basic Specs

- 2000 lumens*
- XGA (1024 x 768)
- 3.9 lbs /1.784 kg
- 500:1 Contrast Ratio
- Digital Keystone Correction
- Aspect Ratio: 4:3 native, 16:9 supported
- 3-Year Standard Warranty



3M[™] Digital Projector X20 Specifications and Accessories

Optical

Brightness: Imager set: Resolution (native): Aspect ratio: Colors: Screen size (range): Zoom/Focus: Zoom ratio. Projection lens: F (focal length): **Optional lenses:** Contrast ratio: Lamp: Lamp Life:

Electrical

Video compatibility:

Component signal:

Automatic Digital Keystone correction: Fixed 6:1 upward shift;

Audio: Noise level: Compatible resolution: Horizontal scan: Vertical scan: Power consumption: Power supply: Universal: Regulatory approvals:

Operating temperature: Storage temperature: Altitude:

**The degrees specified are based on XGA resolution at 60 Hz input and zoom lens position is wide.

2000 lumens (maximum rating) 0.63", P-Si TFT Panel XGA (1024 x 768 pixels) 4:3 native, 16:9 supported 16.7 million 30-300 inches Manual 1.2:1 F 1.8-1.9 (f=16.4 - 19.7 mm) No 500:1 160W UHB 2000 hours (normal), up to 3000 hours (whisper)

NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM 480i, 480p, 525i, 525p, 625i, 576i, 720p, 750p, 1080i, 1125i (through computer input ports) Vertical +/- 30°** 1 x 1W Normal 36dB, Whisper 30dB VGA, SVGA, XGA, SXGA, UXGA 31.5-106 kHZ 56-120 Hz 250W 100-120V/220-240V, 50/60 Hz UL, cUL, FCC Part 15 Class B, CE, EN60950, WEEE 41°-95°F (5°-35°C) -4°-140°F (-20°-60°C) Sea level to 6000 ft. (1,829 m)

Size

Dimensions (W x H x D):

Weight:

10.8 x 2.3 x 8.1 in (274 x 59 x 205mm)** 3.9 lbs/1.784 kg

**dimensions do not include elevator feet

(a) Screen size diagonal		4:3 screen								
		(b) Projection distance				(c) Screen height				
		min.		max.		down		up		
inch	m	m	inch	m	inch	cm	inch	cm	inch	
30	0.8	0.8	30	0.9	36	7	3	39	15	
40	1.0	1.0	40	1.2	48	9	3	52	21	
50	1.3	1.3	50	1.5	61	11	4	65	26	
60	1.5	1.5	61	1.9	73	13	5	78	31	
70	1.8	1.8	71	2.2	85	15	6	91	36	
80	2.0	2.1	81	2.5	97	17	7	105	41	
90	2.3	2.3	91	2.8	110	20	8	118	46	
100	2.5	2.6	102	3.1	122	22	9	131	51	
120	3.0	3.1	122	3.7	147	26	10	157	62	
150	3.8	3.9	153	4.7	183	33	13	196	77	
200	5.1	5.2	204	6.2	245	44	17	261	103	
250	6.4	6.5	255	7.8	306	54	21	327	129	
300	7.6	7.8	306	9.3	368	65	26	392	154	

Note: These sizes are +10 percent. This is due to variations in the maufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

Warranties

3 Years Standard Projector: 1 Year Prorated Lamp: Ultra Value Warranty Enhancement option available: Includes a free lamp, free loaner while unit is being repaired and expedited service.

Available in US only. See www.3m.com/us/meetings/warranties for details on warranties.



Accessories Included

- Power cords (x3 US, UK, Euro)
- RGB computer cable
- RCA/Stereo mini Audio Adapter
- Remote control with 2 AA batteries
- Multi-language User's Manual
- Multi-language Operator's Guide CD
- Lens cap
- Soft Carry Case

Optional Accessories

- Ultra Value Warranty X20 (WX20)
- Replacement Lamp Kit (LKX20)
- Soft Rolling Bag
- Universal Ceiling Mount
- 78-6969-9904-0 78-6969-9903-2 78-6969-9716-8 78-6969-9874-5

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

© 3M 2008 R102008

3M Projection Systems 3M Canada Building A147-5N-01 6801 River Place Blvd. Austin, TX 78726-9000

P.O. Box 5757 London, Ontario, Canada NGA 4T1

3M Mexico, S.A.. de C.V. Apartado Postal 14-139 Mexico, D.F. 07070 Mexico

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of 3 years from the date of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

Hg-LAMP CONTAINS MERCURY. Manage in accord with disposal laws. See www.lamprecycle.org or call 1-800-328-1371 (USA), 1-800-364-3577 (Canada). For product disposal see www.eiae.org

(USA) or www.epsc.ca (Canada)

Specifications subject to change without notice. 3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies