

## StarTech.com 4-poorts gigabit midspan PoE+ injector 802.3at/af

**Merk :** StarTech.com

**Artikelcode:** POEINJ4G

**Productnaam :** 4-poorts gigabit midspan PoE+ injector 802.3at/af



StarTech.com 4-poorts gigabit midspan PoE+ injector 802.3at/af

StarTech.com 4-poorts gigabit midspan PoE+ injector 802.3at/af. Soort: Netwerkzender, Maximaal bereik: 100 m, Overdrachtssnelheid: 2000 Mbit/s. Bekabelingstechnologie: 10/100/1000Base-T(X), Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u. Kleur van het product: Zwart, Materiaal behuizing: Staal, LED-indicatoren: Power over Ethernet (PoE), Stroom. AC-ingangsspanning: 100 - 240 V, Vermogensverbruik (max): 120 W, Spanning: 52 V. Breedte: 70 mm, Diepte: 94 mm, Hoogte: 26 mm



<b>Prestatie</b>		<b>Energie</b>	
Soort *	Netwerkzender	Spanning	52 V
Maximaal bereik *	100 m	Output current	2,31 A
Overdrachtssnelheid	2000 Mbit/s	Power over Ethernet (PoE)	✓
Auto MDIX IEEE	✓	Type stekker	Type M
Auto-negotiation	✓	<b>Eisen aan de omgeving</b>	
Duplex systeem	Volledig	Bedrijfstemperatuur (T-T)	0 - 50 °C
Plug and play	✓	Temperatuur bij opslag	-10 - 70 °C
Mean time between failures (MTBF)	50000 uur	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
<b>Netwerk</b>		<b>Gewicht en omvang</b>	
Bekabelingstechnologie	10/100/1000Base-T(X)	Breedte	70 mm
Netwerkstandaard	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u	Diepte	94 mm
<b>Poorten &amp; interfaces</b>		Hoogte	26 mm
Aantal Ethernet LAN (RJ-45)-poorten	8	Gewicht	204 g
Hoeveelheid Power over Ethernet (PoE) ports	4	<b>Technische details</b>	
Aansluiting voor netstroomadapter	✓	Certificaten van naleving	RoHS
<b>Design</b>		<b>Inhoud van de verpakking</b>	
Kleur van het product	Zwart	Meegeleverde kabels	AC
Materiaal behuizing	Staal	Gebruikershandleiding	✓
LED-indicatoren	Power over Ethernet (PoE), Stroom	Inclusief AC-adapter	✓
Certificering	CE, FCC	<b>Verpakking</b>	
<b>Energie</b>		Breedte verpakking	180 mm
AC-ingangsspanning	100 - 240 V	Diepte verpakking	305 mm
Vermogensverbruik (max)	120 W	Hoogte verpakking	90 mm
		Gewicht verpakking	1,63 kg

**Logistieke gegevens**

Code geharmoniseerd systeem (HS) 85176990



0065030859752



065030859752

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.