



# RUT230 Router

RUT230 is a compact, cost-effective and powerful industrial router for professional applications. Router delivers high performance for mission-critical cellular communication. Equipped with external SIM holder and signal strength status LEDs, it ensures easy network management. External antenna connectors make it possible to attach desired antennas and to easily find the best signal location.



## KEY FEATURES

### HARDWARE

- 1 x SMA for 3G
- 1 x RP-SMA for WiFi
- DIN rail mounting (incl. sideways mounting) (optional)
- 9 - 30 VDC
- External SIM holder
- 1 x WAN
- 1 x LAN
- 1 x Input
- 1 x Output
- WiFi and Mobile LED indications

- OpenVPN
- PPTP
- L2TP
- IPSec
- GRE Tunnel
- Bootloader WebUI
- SMS Control
- WiFi Hotspot
- Backup WAN

- Ping Reboot
- Web Filter
- SNMP
- Configuration profiles
- Dynamic DNS
- Periodic Reboot
- Mobile Quota Control
- NTP
- RMS compatibility

## SPECIFICATIONS

### UMTS/HSPA+

- 900/2100 MHz
- HSDPA mode: 14.5 Mbps (Cat 10) downlink speed
- HSUPA mode: 5.76 Mbps (Cat 6) uplink speed
- UMTS mode: 384 kbps DL, 384 kbps UL
- Power Class 3 (24dBm +1/-3dB) for UMTS bands

### GSM/GPRS/EDGE

- 850/900/1800/1900 Mhz
- GPRS/EDGE Multi-slot Class 12
- Power Class E2 (27dBm ±3dB) for EDGE 850/900
- Power Class E2 (26dBm ±3/-4dB) for EDGE 1800/1900
- Power Class 4 (33dBm ±2dB) for GSM 850/900
- Power Class 1 (30dBm ±2dB) for GSM 1800/1900

### ETHERNET

- IEEE 802.3, IEEE 802.3u standards
- 1 x LAN 10/100Mbps Ethernet port
- 1 x WAN 10/100Mbps Ethernet port
- Supports auto MDI/MDIX

### WiFi

- IEEE 802.11b/g/n WiFi standards
- AP and STA modes
- 64/128-bit WEP, WPA, WPA2, WPA&WPA2 encryption methods
- 2.401-2.483 GHz WiFi frequency range\*
- 20dBm max WiFi TX power
- SSID stealth mode and access control based on MAC address

### HARDWARE

- High performance 400 MHz CPU with 64 Mbytes of DDR2 memory
- External SIM holder
- 4 pin DC connector with 1 x Digital input and 1 x Digital output
- Reset/restore to default button
- 1 x SMA for 3G, 1 x RP-SMA for WiFi antenna connectors
- 2 x Ethernet LEDs, 1 x power LED
- 5 x signal strength LEDs, 2 x connection type indication LEDs
- Bottom and sideways DIN rail mounting slits

### SOFTWARE

- OpenVPN, IPsec, GRE, L2TP, PPTP
- Firmware update from bootloader via WebUI
- SMS Control
- Remote Management System and Teltonika Router App for easy setup, configuration and maintenance.

### ELECTRICAL, MECHANICAL & ENVIRONMENTAL

- Dimensions (W x D x H) 83 mm x 74 mm x 25 mm
- Weight 125 g
- Power supply 100 – 240 VAC -> 9 VDC wall adapter
- Input voltage range 9 – 30VDC
- Power consumption < 5W
- Operating temperature -40 °C to 75 °C
- Storage temperature -45 °C to 80 °C
- Operating humidity 10% to 90% Non-condensing
- Storage humidity 5% to 95% Non-condensing

\*Supported frequency bands are dependent on geographical location and may not be available in all markets.

