


# Delock Riser Card PCI Express x1 > x16 with 60 cm USB cable

## Description

The PCI Express riser card by Delock can be plugged into any PCI Express x1 slot on the motherboard. Then the x16 PCI Express slot can be mounted in a different position in the case. This allows a graphics card to be operated in each PCIe slot of a motherboard, even if the graphics card is wider than a single slot. By using several riser cards, several graphics cards can be operated simultaneously on one motherboard, e.g. for mining crypto currencies such as Bitcoin, Ethereum or Zcash.



## Note

The package content includes a USB 3.0 riser cable with a length of 60 cm. No USB signals are transmitted through this cable, therefore it is not possible to exchange it with a different or longer cable.

## Special features

A PCIe x16 graphics card can be used with a PCIe x1 slot.

## Specification

- Connectors:
  - Motherboard side:
    - 1 x PCI Express x1
    - 1 x USB 3.0 Type-A female
  - Riser side:
    - 1 x PCI Express x16
    - 1 x USB 3.0 Type-A female
    - 1 x 6 pin PCIe power female
- Data transfer rate up to 800 MB/s
- 4 x FP solid capacitors, ensures secure power supply of the graphics card
- 4 x mounting holes on the riser card
- Bottom side with isolating, antislip pad
- Cable data:
  - 1 x riser cable USB 3.0 Type-A male to male ca. 60 cm (incl. connectors)
  - 1 x power cable 6 pin to SATA ca. 20 cm (incl. connectors)
- Dimensions of the riser card (LxWxH): ca. 128.25 x 43.50 x 21.20 mm
- OS independent, no driver installation necessary

## System requirements

- PC with one free PCI Express x1 / x4 / x8 / x16 / x32 slot
- Power supply with a free SATA power connector

## Package content

- PCIe to USB riser card
- USB to PCIe riser card
- USB 3.0 cable
- Power cable

## Item no. 41426


EAN: 4043619414260

Country of origin: China

Package: Retail Box



Images



General	
Supported operating system:	OS independent, no driver installation necessary
Technical characteristics	
Data transfer rate:	up to 800 MB/s
Physical characteristics	
Length:	128.25 mm
Width:	43.50 mm
Height:	21.20 mm