

IPC 3U-30240



IPC 3U-30240

The **IPC 3U-30240** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 3U-30240** provides the possibility to remove the two HDD cages on both sides and therefore to mount up to six 5.25" external hard drives. In the middle four external 3.5" HDDs are also available.

One 120mm and two 60mm fans guarantee an optimal cooling.

Additional extras like easily reachable USB 2.0 connectors and the lid with the snap locks complete this total package.



IPC 3U-30240

Specifications

Motherboard Mini ITX, mATX, Flex-ATX, µATX*, ATX*

maximal motherboard size WxD: 305mm x 191mm, 12" x 7.5"

(*maximal 191mm mounting depth)
1x drive bays 5.25" for 5x 3.5" internal or 3x 5.25" external hard drives **Drive Bays**

2x drive bays 5.25" for 1x 5.25" external or 1x 3.5"

internal or 4x 2.5" internal hard drive/s 1x drive bay 5.25" for 1x 5.25" external or

1x 3.5" internal or 2x 2.5" internal hard drive/s

4x drive bays 3.5" for 1x 3.5" internal or 1x 2.5" internal hard drive

Front Connectors USB 3.0: 1 USB 2.0: 1

Cooling System Front: 1x 120mm

(included, Molex connector)

6x 40mm (optional in the 5.25" drive front bezel)

> Rear: 2x 60mm (included, 3pin connector)

Power-Button Controls Reset-Button

LED Power

HDD Activity 3x Network Activity

Alert

Power Supply ATX PSU Material 1.0/1.2mm Steel

Packing Units Shipping Unit: 1 Piece

Pallet: 24 Pieces

Guarantee and Warranty Case 24 Months Warranty 88887106 Article Number

EAN-Code 4260133126275

Scope of Delivery Screw Set

Mounting rails for 3.5" hard drives

Features HDD cages removable and optional positionalble

Only 5 slot openings + 1 slot with optional Riser Card

1x 120mm and 2x 60mm fan included

USB 3.0 and USB 2.0 as block connector

Lid with snap lock

Lockable frontgrill 3HU black Optional Accessories

(Article number: 88887141)

Dimensions and Weight

	Cage	Case	Package
Height	133.5mm	133.5mm	175mm
Width	433mm	480mm	560mm
Depth	400mm	435mm	560mm
	net): 8.65Kg gross): 10.42	g	

ower supply		
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	_ 4
PCI-Express 6+2Pin		
PCI-Express Con		U۱
IDE 4Pin		-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Certification:

