

DisplayPort Connection Cable

AK-340100-020-S 4016032288930



**DisplayPort connection cable, DP
M/M, 2.0m, w/interlock, Ultra HD 4K, UL, bl**

Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

- 1 Support 4K/2K with 60Hz
- 1 Max. supported Video Resolution: 4096 x 2160p; 1920 x 1080p
- 1 Connector 1: DP, plug
- 1 Connector 2: DP, plug
- 1 DisplayPort standard: DisplayPort 1.2
- 1 UL certified: UL20276
- 1 Hoods: molded
- 1 Shielding: triple shielding
- 1 AWG: 28
- 1 Wire material: CU
- 1 Connector surface: nickel-plated
- 1 Interlock: Snap fastener
- 1 Ferrite filter: none
- 1 Color cable: black
- 1 Color connector: black
- 1 Length: 2 m
- 1 Packaging: Polybag

DisplayPort Connection Cable

AK-340100-020-S 4016032288930

→ Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	60	7,30	50,50	33,00	22,00	36663,00
Packaging Unit Inside	10	1,22	28,00	20,00	9,00	5040,00
Packaging Unit Single	1	0,12	23,00	14,00	2,50	805,00
Net single without Packaging	1	0,00	12,00	14,00	2,50	420,00

