

Delock Adapter USB 2.0 to 4 x serial RS-422/485

Description

This USB 2.0 to serial adapter enables you to connect up to four different serial devices to a free USB port.



Specification

- Chipset: FT4232HL, SP3078EE
- Connector: USB 2.0-B female to 4 x 9 pin serial RS-422/485 male
- 4 x DIP switch: RS-422/485 operation setting
- Internal pin header: Jumper switch terminator on / off
- Serial male connector with screw nuts
- Data transfer rate up to 1 Mb/s
- LED for indication of TxD / RxD activity
- Automatical recognition and switching between RS-422 and RS-485
- ±15KV ESD protection on all signal pins
- Wall mounting integrated in the housing
- Power consumption:
 - operation: ≤ 143 mA / 715 mW
 - standby: 92 mA / 460 mW
- Additional I/O and IRQ are not required
- Dimension: 172 x 65 x 23 (LxWxH)

System requirements

- Windows XP/Vista/Vista-64/7/7-64, Linux ex Kernel 2.6
- PC or Notebook with a free USB port

Item No. 87587



EAN 4043619875870

Country of origin China

Package content

- USB 2.0 to 4 x serial RS-422/485 adapter
- USB 2.0 cable A-B
- 8 jumper
- Driver CD
- User manual

Package

- White Box

Images

