

Delock External USB 3.1 Gen 1 Hub USB Type-C™ > 3 x USB 3.0 Type-A + 1 x USB Type-C™

Description

The USB hub from Delock can be connected via USB Type-C™ interface to a PC or laptop. It has three USB Type-A connectors as well as one USB Type-C™ connector. Different USB devices such as docking stations, card reader, external enclosure etc. can be connected.



Specification

- Connector:
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male >
 - 3 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ female
 - 1 x 5 V DC jack
- Chipset: VL811+
- Data transfer rate up to:
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- USB cable directly on the hub (length ca. 7 cm)
- Dimensions (LxWxH): ca. 91 x 40 x 16 mm
- Use as self-powered (with power supply) or bus-powered (without power supply)
- Electrical power per port:
 - USB Type-C™: max. 15 watt (5 V / 3 A)
 - USB Type-A: max. 4.5 watt (5 V / 0.9 A)
- Plug & Play

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 5 V / 4 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 1.7 mm
 - outside: ø ca. 4.75 mm
 - length: ca. 9.5 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 3.17.x / Kernel 4.x.x, Mac OS 10.11.X
- PC or laptop with a free USB Type-C™ port

Package content

- Hub USB
- External power supply
- User manual

Item no. 62537

EAN: 4043619625376

Country of origin: China

Package: Retail Box



Images



General	
Function:	Plug & Play
Specification:	USB 3.0
Supported operating system:	Mac 10.11 Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit ex Linux Kernel 3.17 ex Linux Kernel 4.x.x
Interface	
Connector 1:	1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male
Connector 2:	3 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
connector 3:	1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ female
connector 4:	1 x 5 V DC jack
Technical characteristics	
Chipset:	VL811+
Data transfer rate:	5 Gbps
Physical characteristics	
Length:	91 mm
Width:	40 mm
Height:	16 mm
Colour:	black
Power supply	
Input:	AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
Output:	5 V / 4 A
Connector:	DC plug 4.75 mm x 1.70 mm