



## LevelOne FEP-0511 netwerk-switch Fast Ethernet (10/100) Power over Ethernet (PoE) Grijs

**Merk :** LevelOne

**Artikelcode:** FEP-0511

**Productnaam :** FEP-0511



LevelOne FEP-0511. Type basis-switching RJ-45 Ethernet-poorten: Fast Ethernet (10/100), Aantal basis-switching RJ-45 Ethernet-poorten: 5. Full duplex. MAC-adrestabel: 1000 entries. Netwerkstandaard: IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE)



| Poorten & interfaces                            |  | Power over Ethernet (PoE)                       |                 |
|---|--|---|-----------------|
| Aantal basis-switching RJ-45 Ethernet-poorten * | 5  | Aantal Power over Ethernet plus (PoE +)-poorten | 4               |
| Type basis-switching RJ-45 Ethernet-poorten *   | Fast Ethernet (10/100)   | Vermogen per poort Power over Ethernet (PoE)    | 30 W            |
| <b>Netwerk</b>                                  |  | Totaal Power over Ethernet (PoE)-budget         | 62 W            |
| Netwerkstandaard *                              | IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x | <b>Eisen aan de omgeving</b>                    |                 |
| 10G support *                                   | ✗  | Bedrijfstemperatuur (T-T)                       | 0 - 40 °C       |
| Koperen ethernetbekabelingstechnologie          | 10BASE-T, 100BASE-TX   | Relatieve vochtigheid in bedrijf (V-V)          | 10 - 90 procent |
| Full duplex                                     | ✓  | Luchtvochtigheid bij opslag                     | 10 - 90 procent |
| Datastroombeheer                                | ✓  | <b>Gewicht en omvang</b>                        |                 |
| Auto MDI/MDI-X                                  | ✓  | Breedte   | 122 mm          |
| Auto-negotiation                                | ✓  | Diepte  | 44 mm           |
| <b>Data-uitwisseling</b>                        |  | Hoogte  | 160 mm          |
| MAC-adrestabel *                                | 1000 entries   | Gewicht   | 800 g           |
| Store-and-forward                               | ✓  | <b>Verpakking</b>                               |                 |
| Packet forwarding rate (100 Mbps)               | 148000 pps   | Meegeleverde kabels                             | AC              |
| Packet forwarding rate (10 Mbps)                | 14880 pps  | Snelstartgids                                   | ✓               |
| <b>Design</b>                                   |  | Type verpakking                                 | Doos            |
| Kleur van het product                           | Grijs  | Breedte verpakking                              | 145 mm          |
| LED-indicatoren                                 | Activiteit, Power over Ethernet (PoE), Stroom                    | Diepte verpakking                               | 80 mm           |
| Land van herkomst                               | Taiwan   | Hoogte verpakking                               | 235 mm          |
| <b>Prestatie</b>                                |  | Gewicht verpakking                              | 1,1 kg          |
| Buffergrootte                                   | 48 KB  | <b>Logistieke gegevens</b>                      |                 |
| <b>Energie</b>                                  |  | (Buitenste) hoofdverpakking breedte             | 310 mm          |
| AC-ingangsspanning                              | 100 - 240 V  | (Buitenste) hoofdverpakking lengte              | 252 mm          |
| AC-ingangsfrequentie                            | 50 - 60 Hz   | (Buitenste) hoofdverpakking hoogte              | 422 mm          |
| Stroom  | 2 A  | Code geharmoniseerd systeem (HS)                | 85176990        |
| Stroomverbruik (typisch)                        | 65 W   | (Buitenste) hoofdverpakking brutogewicht        | 12,5 kg         |
| Stroomspanning bescherming                      | Overstroom   | Hoeveelheid per (buitenste) hoofdverpakking     | 10 stuk(s)      |
| <b>Power over Ethernet (PoE)</b>                |  |   |                 |
| Power over Ethernet (PoE) *                     | ✓  |   |                 |



4015867195840

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date