



LevelOne GVM-1220 netwerk media converter 1000 Mbit/s 1310 nm Single-mode Zwart

Merk : LevelOne

Artikelcode: GVM-1220

Productnaam : GVM-1220



- Vezel met enkelvoudige modus met SC-connector voor transmissie van tot 20 km
- Supports Operations, Administration, and Maintenance (OAM) mechanisms
- Web gebaseerde- en SNMP-beheer
- Ingebouwde LFP (Link Fault Pass-through) (LLCF/LLR) -technologie
- Ondersteunt op (Tag gebaseerde, Q-inQ)
- IEEE 802.3x datatransport-besturing beschermt tegen lost packets voor betrouwbare dataoverdracht

1 x RJ-45, 1 x SC/ST/FC, 100~240VAC, 20 km, 720 g
 LevelOne GVM-1220. Maximale overdrachtssnelheid van gegevens: 1000 Mbit/s, Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet interface type: Gigabit Ethernet. Vezel-optische connector: FC, SC, ST, Connectiviteitstechnologie: Bedraad. Maximaal bereik: 20000 m, Golfengte: 1310 nm, Draad modus structuur: Single-mode. LED-indicatoren: Activiteit, FDX, Link, Stroom, Kleur van het product: Zwart, Land van herkomst: China. Ingangsspanning: 100 - 240 V, Spanning: 5 V, Output current: 2 A



Netwerk		Energie	
Maximale overdrachtssnelheid van gegevens *	1000 Mbit/s	Ingangsspanning	100 - 240 V
Netwerkstandaard	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Spanning	5 V
Ethernet interface type	Gigabit Ethernet	Output current	2 A
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Beheerfuncties	
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Web-gebaseerd management	✓
Fiber ethernet cabling technologie	1000BASE-X	Gewicht en omvang	
Jumbo Frames ondersteuning	✓	Breedte	127 mm
Jumbo frames	9000	Diepte	156 mm
Datastroombeheer	✓	Hoogte	32 mm
VLAN=ondersteuning	✓	Gewicht	720 g
Store-and-forward	✓	Eisen aan de omgeving	
Duplex systeem	Volledig, Half	Bedrijfstemperatuur (T-T)	-10 - 55 °C
		Relatieve vochtigheid in bedrijf (V-V)	5 - 90 procent
Poorten & interfaces		Verpakking	
Connectiviteitstechnologie	Bedraad	Breedte verpakking	185 mm
Aantal Ethernet LAN (RJ-45)-poorten	1	Diepte verpakking	275 mm
Fibre channel-poorten	1	Hoogte verpakking	62 mm
Vezel-optische connector *	FC, SC, ST	Gewicht verpakking	880 g
		Type verpakking	Doos
Prestatie		Technische details	
Maximaal bereik *	20000 m	Certificaten van naleving	RoHS
Golfengte *	1310 nm	Logistieke gegevens	
Draad modus structuur	Single-mode	Code geharmoniseerd systeem (HS)	85176990
Mean time between failures (MTBF)	30000 uur	(Buitenste) hoofdverpakking breedte	360 mm
		(Buitenste) hoofdverpakking lengte	480 mm
Design		(Buitenste) hoofdverpakking hoogte	390 mm
Intern *	✗	(Buitenste) hoofdverpakking brutogewicht	17,5 kg
LED-indicatoren	Activiteit, FDX, Link, Stroom	Hoeveelheid per (buitenste) hoofdverpakking	17 stuk(s)
Kleur van het product	Zwart		
Land van herkomst	China		
Certificering	CE, FCC		



4015867195406

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date