



## LevelOne GVT-2010 netwerk media converter Zwart

**Merk :** LevelOne

**Artikelcode:** GVT-2010

**Productnaam :** GVT-2010

LevelOne GVT-2010. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s, Koperen ethernetbekabelingstechnologie: 100BASE-TX, 1000BASE-T. Vezel-optische connector: SFP, Connectiviteitstechnologie: Bedraad. Mean time between failures (MTBF): 30000 uur. LED-indicatoren: Activiteit, FDX, Link, Stroom, Kleur van het product: Zwart, Certificering: CE, FCC. Ingangsspanning: 90 - 264 V, Spanning: 5 V, Output current: 2 A



Netwerk		Design	
Netwerkstandaard	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Certificering	CE, FCC
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	<b>Energie</b>	
Koperen ethernetbekabelingstechnologie	100BASE-TX, 1000BASE-T	Ingangsspanning	90 - 264 V
Fiber ethernet cabling technologie	1000BASE-LX, 1000BASE-SX	Spanning	5 V
Jumbo Frames ondersteuning	✓	Output current	2 A
Jumbo frames	9000	<b>Beheerfuncties</b>	
Datastroombeheer	✓	Web-gebaseerd management	✓
VLAN=ondersteuning	✓	<b>Gewicht en omvang</b>	
Auto MDI/MDI-X	✓	Breedte	94 mm
Store-and-forward	✓	Diepte	71 mm
Duplex systeem	Volledig, Half	Hoogte	26 mm
<b>Poorten &amp; interfaces</b>		Gewicht	220 g
Connectiviteitstechnologie	Bedraad	<b>Eisen aan de omgeving</b>	
Aantal Ethernet LAN (RJ-45)-poorten	1	Bedrijfstemperatuur (T-T)	-10 - 60 °C
Fibre channel-poorten	1	Temperatuur bij opslag	-40 - 85 °C
Vezel-optische connector *	SFP	Relatieve vochtigheid in bedrijf (V-V)	5 - 90 procent
Aantal Power over Ethernet plus (PoE +)-poorten	1	<b>Verpakking</b>	
<b>Prestatie</b>		Breedte verpakking	120 mm
Mean time between failures (MTBF)	30000 uur	Diepte verpakking	55 mm
<b>Design</b>		Hoogte verpakking	235 mm
Intern *	✗	Gewicht verpakking	430 g
LED-indicatoren	Activiteit, FDX, Link, Stroom	<b>Inhoud van de verpakking</b>	
Kleur van het product	Zwart	Gebruikershandleiding	✓
		<b>Technische details</b>	
		Certificaten van naleving	RoHS
		<b>Logistieke gegevens</b>	
		Code geharmoniseerd systeem (HS)	85176990



4015867195192

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date