



# Delock HDMI Audio Extractor 4K 30 Hz

## Description

This adapter by Delock can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.



ltem no. 62692

EAN: 4043619626922

Country of origin: China

Package: Box



# Specification

## Connectors:

#### Input:

- 1 x HDMI-A 19 pin female
- 1 x 5 V DC jack 2.1 x 5.5 mm

#### Output:

- 1 x HDMI-A 19 pin female
- 1 x 3.5 mm 3 pin stereo jack female (audio)
- 1 x TOSLINK female S/PDIF
- 1 x RCA female S/PDIF
- Switchable between stereo and 5.1 channel
- High Speed HDMI, 3D and HDCP 1.4
- Output with HDMI repeater function
- Resolution up to 3840 x 2160 @ 30 Hz (8 bit), 1920 x 1080 @ 60 Hz (12 bit)
- Video bandwidth up to 300 MHz / 3 Gb/s per channel, 9 Gb/s max.
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- · CEC and HDMI audio routed to the output (pass-through)
- Chipset: CS4344, 24 bit / 192 kHz
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 71 x 61 x 21 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions: inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

## System requirements

A free HDMI-A female

# Package content

- HDMI Audio Extractor
- Mounting brackets and screws





- USB power cable, length: ca. 0.5 m
- Power supply
- User manual

Images







General	
Specification:	DTS Audio
	High Speed HDMI
	Dolby Digital
	HDCP 1.4
	LPCM
Interface	
Output:	1 x 3.5 mm 3 pin stereo jack female
	1 x RCA female
	1 x HDMI-A 19 pin female
	1 x TOSLINK female
Input:	1 x HDMI-A 19 pin female
	1 x 5 V DC female 5,5 mm x 2,1 mm
Technical characteristics	
Chipset:	Cirrus CS4344
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Video bandwidth:	300 MHz
Physical characteristics	
Housing colour:	black
Housing material:	metal
Length:	71 mm
Width:	61 mm
Height:	21 mm
Power supply	
Туре:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.3 A
Output:	5 V / 1 A
Connector:	DC male 5.5 mm x 2.1 mm
Cable length:	1 m