



LevelOne FVM-1101 netwerk media converter 100 Mbit/s 1310 nm Zwart

Merk : LevelOne

Artikelcode: FVM-1101

Productnaam : FVM-1101

LevelOne FVM-1101. Maximale overdrachtssnelheid van gegevens: 100 Mbit/s, Converter input interface: 10Base-T, 100Base-TX, Converter output interface: 100Base-FX. Vezel-optische connector: LC, SC, ST, Connectiviteitstechnologie: Bedraad. Maximaal bereik: 2000 m, Golflengte: 1310 nm. LED-indicatoren: Activiteit, FDX, Link, Stroom, Kleur van het product: Zwart, Land van herkomst: China. Ingangsspanning: 100 - 240 V, Spanning: 5 V, Output current: 2 A



Netwerk		Energie	
Maximale overdrachtssnelheid van gegevens *	100 Mbit/s	Output current	2 A
Converter input interface	10Base-T, 100Base-TX	Beheerfuncties	
Converter output interface	100Base-FX	Web-gebaseerd management	✓
Netwerkstandaard	IEEE 802.3, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x	Gewicht en omvang	
Ethernet interface type	Fast Ethernet	Breedte	127 mm
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Diepte	156 mm
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-FX, 100BASE-TX	Hoogte	32 mm
Jumbo Frames ondersteuning	✓	Gewicht	720 g
Jumbo frames	9000	Eisen aan de omgeving	
Datastroombeheer	✓	Bedrijfstemperatuur (T-T)	-10 - 55 °C
VLAN=ondersteuning	✓	Relatieve vochtigheid in bedrijf (V-V)	5 - 90 procent
Store-and-forward	✓	Verpakking	
Duplex systeem	Volledig, Half	Breedte verpakking	185 mm
Poorten & interfaces		Diepte verpakking	275 mm
Connectiviteitstechnologie	Bedraad	Hoogte verpakking	62 mm
Aantal Ethernet LAN (RJ-45)-poorten	1	Gewicht verpakking	880 g
Fibre channel-poorten	1	Type verpakking	Doos
Vezel-optische connector *	LC, SC, ST	Technische details	
Prestatie		Certificaten van naleving	RoHS
Maximaal bereik *	2000 m	Logistieke gegevens	
Golflengte *	1310 nm	Code geharmoniseerd systeem (HS)	85176990
Design		(Buitenste) hoofdverpakking breedte	360 mm
LED-indicatoren	Activiteit, FDX, Link, Stroom	(Buitenste) hoofdverpakking lengte	480 mm
Kleur van het product	Zwart	(Buitenste) hoofdverpakking hoogte	390 mm
Land van herkomst	China	(Buitenste) hoofdverpakking brutogewicht	17,5 kg
Certificering	FCC, CE	Hoeveelheid per (buitenste) hoofdverpakking	17 stuk(s)
Energie			
Ingangsspanning	100 - 240 V		
Spanning	5 V		



4015867195529

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-SEP-2024. Prints or copies of Information are only valid on the printed Publication date