



LevelOne GVM-1000 netwerk media converter 1000 Mbit/s Zwart

Merk : LevelOne

Artikelcode: GVM-1000

Productnaam : GVM-1000

LevelOne GVM-1000. Maximale overdrachtsnelheid van gegevens: 1000 Mbit/s, Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet interface type: Gigabit Ethernet. Vezel-optische connector: SFP, Connectiviteitstechnologie: Bedraad. Mean time between failures (MTBF): 30000 uur. LED-indicatoren: Activiteit, FDX, Link, Stroom, Kleur van het product: Zwart, Land van herkomst: China. Ingangsspanning: 100 - 240 V, Spanning: 5 V, Output current: 2 A



Netwerk		Energie	
Maximale overdrachtsnelheid van gegevens *	1000 Mbit/s	Spanning	5 V
Netwerkstandaard	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ah, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Output current	2 A
Ethernet interface type	Gigabit Ethernet	Beheerfuncties	
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Web-gebaseerd management	✓
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Hot-swap	✓
Jumbo Frames ondersteuning	✓	Gewicht en omvang	
Jumbo frames	9000	Breedte	127 mm
Datastroombeheer	✓	Diepte	156 mm
VLAN=ondersteuning	✓	Hoogte	32 mm
Store-and-forward	✓	Gewicht	700 g
Duplex systeem	Volledig, Half	Eisen aan de omgeving	
Link Loss Carry Forward (LLCF) ondersteund	✓	Bedrijfstemperatuur (T-T)	-10 - 55 °C
Link Loss Return (LLR) ondersteund	✓	Relatieve vochtigheid in bedrijf (V-V)	5 - 90 procent
Poorten & interfaces		Verpakking	
Connectiviteitstechnologie	Bedraad	Breedte verpakking	185 mm
Aantal Ethernet LAN (RJ-45)-poorten	1	Diepte verpakking	275 mm
Fibre channel-poorten	1	Hoogte verpakking	62 mm
Vezel-optische connector *	SFP	Gewicht verpakking	860 g
Prestatie		Inhoud van de verpakking	
Mean time between failures (MTBF)	30000 uur	Gebruikershandleiding	✓
Design		Technische details	
Intern *	✗	Duurzaamheidscertificaten	RoHS
LED-indicatoren	Activiteit, FDX, Link, Stroom	Logistieke gegevens	
Kleur van het product	Zwart	Code geharmoniseerd systeem (HS)	85176990
Land van herkomst	China	(Buitenste) hoofdverpakking breedte	360 mm
Certificering	CE, FCC	(Buitenste) hoofdverpakking lengte	480 mm
Energie		(Buitenste) hoofdverpakking hoogte	390 mm
Ingangsspanning	100 - 240 V	(Buitenste) hoofdverpakking brutogewicht	17,5 kg

Logistieke gegevens

Hoeveelheid per (buitenste)
hoofdverpakking 17 stuk(s)



4015867195628

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAR-2024. Prints or copies of Information are only valid on the printed Publication date