

Shaping the perfection

ABS plastic filament for 3D printers, 1.75 mm diameter, 0.6 kg, green color, 53 mm spool

FF-3DP-ABS1.75-02-G

VERSATILE & EASY TO USE

- Acrylonitrile butadiene styrene (ABS) is a common thermoplastic strong and durable plastic available in a range of colors.
- ABS is the plastic used in lots of things around us and is perfect for heated plastic extrusion 3D printing.





Specifications

Material: ABS, 1.75 mm diameter Weight: 0.6 kg/spool Density at 215°C: 1.05 g/cm3 Melt Flow Index at g/10min, 220°C/ 5kg: 1.8 Melt Point: 210 250 °C Heat-Deflection-Temperature at 0.455 MPa: 85 100 °C Yield Strength at 5mm/min: 45 MPa Impact Strength: 18 KJ/m2 Ensile Break: 25 % Diameter: 1.75 ± 0.05 mm

Features

- ABS filament with 1.75 mm diameter
- Excellent chemical resistance
- High Stiffness and good impact resistance at low temperatures
- Easily processed with good surface finish
- Can be used in a variety of 3D printers
- 0.6 kg spool

Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 12 0.03 10.22 210x210x90 mm 360x360x230 mm CN 8716309091572 3916909000

System requirements

A 3D printer with 1.75 mm extruder of temperature around 230 $^{\circ}\text{C},$ suitable for PLA filament

Certificates



Copyright © 2009–2017, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588 | www.gembird.nl | postmaster@gembird.n