

NETGEAR XS505M Unmanaged 10G Ethernet (100/1000/10000)
Grijs, Zilver

Merk : NETGEAR

Artikelcode: XS505M-100EUS

Productnaam : XS505M



NETGEAR XS505M. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: 10G Ethernet (100/1000/10000), Aantal basis-switching RJ-45 Ethernet-poorten: 4. Full duplex. MAC-adrestabel: 2000 entries, Switchingcapaciteit: 100 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3aq, IEEE 802.3az,.... Netstekker: DC-in ingang. Rack-montage

Beheerfuncties		Design	
Switch type *	Unmanaged	Certificering	47 CFR FCC, ICES-003:2016 Issue 6, ANSI C63.4:2014, EN 55032:2012+AC2013, EN 55024:2010, EN 61000-3-2:2014, EN 6100-3-3:2013, AS/NZS CISPR 32:2015, VCCI V-3/2015.04, V-4/2012.4, CNS 13438
Quality of Service (QoS)	✓		
Poorten & interfaces			
Aantal basis-switching RJ-45 Ethernet-poorten *	4		
Type basis-switching RJ-45 Ethernet-poorten *	10G Ethernet (100/1000/10000)		
Aantal moduleslots SPF+	1	Prestatie	Mean time between failures (MTBF) 1093237 uur
Netstekker	DC-in ingang		
Netwerk		Energie	
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3aq, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Stroombron *	AC
		AC-ingangsspanning	100 - 240 V
		AC-ingangsfrequentie	50 - 60 Hz
		Stroom	1.5 A
		Stroomverbruik (typisch)	12,25 W
10G support *	✓	Vermogensverbruik (max)	22,5 W
Full duplex	✓	Power over Ethernet (PoE)	
Datastroombeheer	✓	Power over Ethernet (PoE) *	✗
Data-uitwisseling		Eisen aan de omgeving	
Switchingcapaciteit *	100 Gbit/s	Bedrijfstemperatuur (T-T)	0 - 50 °C
MAC-adrestabel *	2000 entries	Temperatuur bij opslag	-20 - 70 °C
Jumbo Frames ondersteuning	✓	Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
Jumbo frames	9000	Luchtvochtigheid bij opslag	0 - 95 procent
Packet buffergeheugen	128 MB	Hoogte, in bedrijf	0 - 3000 m
Design		Warmtedissipatie	85,3 BTU/h
Rack-montage *	✓	Gewicht en omvang	
Kleur van het product	Grijs, Zilver	Breedte	328 mm
LED-indicatoren	✓	Diepte	169 mm
Veiligheid	CE: CB 60950-1, LVD 60950-1, AUS/NZ: AS/NZS 60950-1, USA: UL 60950-1, SNE VA, BSMI	Hoogte	43,2 mm
		Gewicht	1,38 kg
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS)	85176990



0606449131130



606449131130

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.