LevelOne FEP-0800W120 netwerk-switch Fast Ethernet (10/100) Power over Ethernet (PoE) Grijs

Merk : LevelOne

Artikelcode: FEP-0800W120

Productnaam : FEP-0800W120

LevelOne FEP-0800W120. Type basis-switching RJ-45 Ethernet-poorten: Fast Ethernet (10/100), Aantal basis-switching RJ-45 Ethernet-poorten: 8. Full duplex. MAC-adrestabel: 1000 entries, Switchingcapaciteit: 1,6 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3u, IEEE 802.3x. Netstekker: DC-in ingang. Power over Ethernet (PoE)

Poorten & interfaces	
Aantal basis-switching RJ-45 Ethernet-poorten *	8
Type basis-switching RJ-45 Ethernet-poorten *	Fast Ethernet (10/100)
Netstekker	DC-in ingang

Netwerk	
Netwerkstandaard *	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
10G support *	✗
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX
Full duplex	✓
Datastroombeheer	✓
Auto MDI/MDI-X	✓
Auto-negotiation	✓

Data-uitwisseling	
Switchingcapaciteit *	1,6 Gbit/s
MAC-adrestabel *	1000 entries
Store-and-forward	✓
Packet forwarding rate (100 Mbps)	148000 pps
Packet forwarding rate (10 Mbps)	14880 pps

Design	
Rack-montage *	✗
Kleur van het product	Grijs
LED-indicatoren	Activiteit, Power over Ethernet (PoE), Stroom
Aan/uitschakelaar	✓
Land van herkomst	Taiwan
Certificering	FCC, CE, RoHS

Prestatie	
Buffergrootte	64 KB
Plug and play	✓

Energie	
Ingangsspanning	56 V
Stroomverbruik (typisch)	120 W
Stroomspanning bescherming	Overstroom

Power over Ethernet (PoE)	
Hoeveelheid Power over Ethernet (PoE) ports	8
Vermogen per poort Power over Ethernet (PoE)	30 W
Totaal Power over Ethernet (PoE)-budget	115 W

Eisen aan de omgeving	
Bedrijfstemperatuur (T-T)	0 - 45 °C
Temperatuur bij opslag	-40 - 75 °C
Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Luchtvochtigheid bij opslag	10 - 90 procent

Gewicht en omvang	
Breedte	165 mm
Diepte	99 mm
Hoogte	41 mm
Gewicht	1,4 kg

Verpakking	
Meegeleverde kabels	AC
Gebruikershandleiding	✓
Inclusief AC-adapter	✓
Type verpakking	Doos
Breedte verpakking	371 mm
Diepte verpakking	230 mm
Hoogte verpakking	82 mm
Gewicht verpakking	1,6 kg

Logistieke gegevens	
(Buitenste) hoofdverpakking breedte	525 mm
(Buitenste) hoofdverpakking lengte	246 mm
(Buitenste) hoofdverpakking hoogte	392 mm
Code geharmoniseerd systeem (HS)	85176990
(Buitenste) hoofdverpakking brutogewicht	10 kg
Hoeveelheid per (buitenste) hoofdverpakking	6 stuk(s)

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✓

4015867199749

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-MAR-2024. Prints or copies of Information are only valid on the printed Publication date