



LevelOne GEP-2682 netwerk-switch Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE)

Merk : LevelOne

Artikelcode: GEP-2682



Productnaam : GEP-2682

LevelOne GEP-2682. Switch type: Managed, Switch-laag: L3. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 24, Console port: RJ-45. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 52 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Power over Ethernet (PoE). Rack-montage



Beheerfuncties		Design	
Switch type *	Managed	Certificering	CE, FCC Part 15 Class A
Switch-laag	L3	Prestatie	
Quality of Service (QoS)	✓	Intern geheugen	128 MB
Web-gebaseerd management	✓	Flash memory	32 MB
System event log	✓	Upgraden van firmware mogelijk	✓
Poorten & interfaces		Buffergrootte	512 KB
Aantal basis-switching RJ-45 Ethernet-poorten *	24	Telnet	✓
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	sFlow	✓
Aantal Gigabit Ethernet (koper)-poorten	24	Mean time between failures (MTBF)	211272 uur
Aantal Combo SFP-poorten	2	Energie	
Console port	RJ-45	AC-ingangsspanning	100 - 240 V
Netwerk		AC-ingangsfrequentie	50 - 60 Hz
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Stroomverbruik (typisch)	20,71 W
10G support *	✗	Power over Ethernet (PoE)	
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) *	✓
Datastroombeheer	✓	Aantal Power over Ethernet plus (PoE +)-poorten	24
Verbindingsaggregatie	✓	Vermogen per poort Power over Ethernet (PoE)	30 W
Broadcast stormbeheer	✓	Totaal Power over Ethernet (PoE)-budget	370 W
Spanning tree protocol	✓	Eisen aan de omgeving	
Kabellengtedetectie	✓	Bedrijfstemperatuur (T-T)	0 - 45 °C
VLAN=ondersteuning	✓	Temperatuur bij opslag	-20 - 70 °C
Virtuele LAN-functies	Private VLAN, Tagged VLAN, MAC address-based VLAN, Port-based VLAN	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Optische vezel		Luchtvochtigheid bij opslag	10 - 90 procent
Fiber ethernet cabling technologie	1000BASE-X	Gewicht en omvang	
Data-uitwisseling		Breedte	442 mm
Switchingcapaciteit *	52 Gbit/s	Diepte	211 mm
Verzending snelheid	38,7 Mpps	Hoogte	44 mm
		Gewicht	3,5 kg
		Verpakking	
		Meegeleverde kabels	AC, LAN (RJ-45)
		Snelstartgids	✓
		Type verpakking	Blister

Data-uitwisseling		Verpakking	
MAC-adrestabel *	8000 entries	Ondersteunings-cd	✓
Store-and-forward	✓	Breedte verpakking	300 mm
Statische route	✓	Diepte verpakking	520 mm
Jumbo Frames ondersteuning	✓	Hoogte verpakking	90 mm
Jumbo frames	9600	Gewicht verpakking	3,9 kg
Beveiliging		Logistieke gegevens	
DHCP-functies	DHCP server, DHCP snooping, DHCP relay, DHCP client	(Buitenste) hoofdverpakking breedte	482 mm
Access Control List (ACL)	✓	(Buitenste) hoofdverpakking lengte	540 mm
IGMP snooping	✓	(Buitenste) hoofdverpakking hoogte	324 mm
Ondersteunde beveiligingsalgoritmen	802.1x RADIUS	Code geharmoniseerd systeem (HS)	85176990
SSH/SSL support	✓	(Buitenste) hoofdverpakking brutogewicht	20,7 kg
Bescherming lus	✓	Hoeveelheid per (buitenste) hoofdverpakking	5 stuk(s)
BPDU filtering / bescherming	✓		
Protocollen			
Ondersteunde netwerkprotocollen	IPv4/IPv6		
GARP VLAN Registratieprotocol (GVRP)	✓		
Design			
Rack-montage *	✓		
LED-indicatoren	Activiteit, Link, Power over Ethernet (PoE), Snelheid, Systeem		
Land van herkomst	Taiwan		
Veiligheid	CB IEC-60950, UL 60950-1, 2nd Edition, 2014-10-14, CAN/CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-10		



4015867198971

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date