

NETGEAR GS110MX Unmanaged 10G Ethernet (100/1000/10000) Zwart

Merk : NETGEAR

Artikelcode: GS110MX-100PES

Productnaam : GS110MX

NETGEAR GS110MX. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: 10G Ethernet (100/1000/10000), Aantal basis-switching RJ-45 Ethernet-poorten: 10. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 56 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3x. DC voltage input: 13.2 V. Netstekker: DC-in ingang. Rack-montage



Beheerfuncties		Design	
Switch type *	Unmanaged	Rack-montage *	✓
Quality of Service (QoS)	✓	Kleur van het product	Zwart
MIB-ondersteuning	✓	LED-indicatoren	✓
Poorten & interfaces		Veiligheid	UL 60950-1/CAN/CSA C22.2 No. 60960-1-07 EN 60950-1: 2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 IEC 60950-1:2005 (ed.2)+A1:2009+A2:2013 AS/NZS 60950.1:2015
Aantal basis-switching RJ-45 Ethernet-poorten *	10		
Type basis-switching RJ-45 Ethernet-poorten *	10G Ethernet (100/1000/10000)		
Aantal Gigabit Ethernet (koper)-poorten	8	Certificering	47 CFR FCC, ICES-003:2016, ANSI C63.4:2014, EN 55032:2012 +AC:2013, CISPR 32:2012, AS/NZS CISPR 32:2013, EN 55032:2015 +AC:2016, CISPR 32:2015 +COR1:2016, AS/NZS CISPR 32:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010 +A1:2015, AS/NZS CISPR 32:2015, VCCI-CISPR 32:2016,
Netstekker	DC-in ingang		
Netwerk		Energie	Stroombron * DC DC voltage input 13.2 V Stroomverbruik (typisch) 4,8 W Vermogensverbruik (max) 6,6 W
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3x		
10G support *	✓		
Datastroombeheer	✓		
Verbindingsaggregatie	✓		
Broadcast stormbeheer	✓		
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s		
VLAN=ondersteuning	✓		
Data-uitwisseling		Power over Ethernet (PoE)	Power over Ethernet (PoE) * ✗
Switchingcapaciteit *	56 Gbit/s		
MAC-adrestabel *	16000 entries		
Aantal trunks	8		
Statische route	✓		
Beveiliging		Eisen aan de omgeving	Bedrijfstemperatuur (T-T) 0 - 40 °C Temperatuur bij opslag -20 - 70 °C Relatieve vochtigheid in bedrijf (V-V) 0 - 90 procent Luchtvochtigheid bij opslag 0 - 95 procent Hoogte, in bedrijf 0 - 3000 m Warmtedissipatie 45,14 BTU/h
Jumbo Frames ondersteuning	✓		
Jumbo frames	10240		
IGMP snooping	✓		
Multicast-functies		Gewicht en omvang	Breedte 236 mm Diepte 102 mm Hoogte 27 mm Gewicht 740 g
Multicast-ondersteuning	✓		
Logistieke gegevens			
Code geharmoniseerd systeem (HS) 85176990			



0606449128871



606449128871

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.