



LevelOne FSW-0503W90 netwerk-switch Fast Ethernet (10/100) Power over Ethernet (PoE) Grijs

Merk : LevelOne

Artikelcode: FSW-0503W90

Productnaam : FSW-0503W90



LevelOne FSW-0503W90. Type basis-switching RJ-45 Ethernet-poorten: Fast Ethernet (10/100), Aantal basis-switching RJ-45 Ethernet-poorten: 4, Console port: RJ-45. Full duplex. MAC-adrestabel: 1000 entries. Netwerkstandaard: IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x. DC voltage input: 56 V. Netstekker: DC-in ingang. Power over Ethernet (PoE). Rack-montage



Poorten & interfaces		Power over Ethernet (PoE)	
Aantal basis-switching RJ-45 Ethernet-poorten *	4	Hoeveelheid Power over Ethernet (PoE) ports	4
Type basis-switching RJ-45 Ethernet-poorten *	Fast Ethernet (10/100)	Vermogen per poort Power over Ethernet (PoE)	15,4 W
Console port	RJ-45	Totaal Power over Ethernet (PoE)-budget	87 W
Netstekker	DC-in ingang		
Netwerk		Eisen aan de omgeving	
Netwerkstandaard *	IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x	Bedrijfstemperatuur (T-T)	0 - 45 °C
10G support *	✗	Temperatuur bij opslag	-40 - 70 °C
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Ondersteundende kabel types	Cat3, Cat4, Cat5	Luchtvochtigheid bij opslag	10 - 90 procent
Full duplex	✓	Gewicht en omvang	
Datastroombeheer	✓	Breedte	90 mm
Auto MDI/MDI-X	✓	Diepte	120 mm
Auto-negotiation	✓	Hoogte	28 mm
Data-uitwisseling		Gewicht	800 g
MAC-adrestabel *	1000 entries	Verpakking	
Store-and-forward	✓	Gebruikershandleiding	✓
Packet forwarding rate (100 Mbps)	148000 pps	Type verpakking	Doos
Packet forwarding rate (10 Mbps)	14880 pps	Breedte verpakking	141 mm
Design		Diepte verpakking	234 mm
Rack-montage *	✓	Hoogte verpakking	79 mm
Kleur van het product	Grijs	Gewicht verpakking	1,04 kg
LED-indicatoren	Link, Power over Ethernet (PoE), Stroom, Uplink	Logistieke gegevens	
Land van herkomst	Taiwan	(Buitenste) hoofdverpakking breedte	430 mm
Certificering	FCC, CE, RoHS	(Buitenste) hoofdverpakking lengte	480 mm
		(Buitenste) hoofdverpakking hoogte	320 mm
Prestatie		Code geharmoniseerd systeem (HS)	85176990
Buffergrootte	48 KB	(Buitenste) hoofdverpakking brutogewicht	18 kg
Energie		Hoeveelheid per (buitenste) hoofdverpakking	20 stuk(s)
DC voltage input	56 V		
Stroomverbruik (typisch)	90 W		
Power over Ethernet (PoE)			
Power over Ethernet (PoE) *	✓		



4015867199961

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-SEP-2024. Prints or copies of Information are only valid on the printed Publication date