Fluke MicroScanner² Cable Verifier Professional Kit

ACT-MS2-KIT 4016032358893



www.assmann.com 1/3

MicroScanner2 Cable Verifier Professional Kit includes MicroScanner2, Main Wiremap Adapter batteries, guide, cables

Next-generation MicroScanner verifies voice/data/video cable and services with an oversized display with revolutionary user interface.

The MicroScanner² Cable Verifier presents a revolutionary change in voice, data, and video cable testing. It starts by taking results from what was four differenttest modes and displaying them all at once – graphical wiremap, pair lengths, distance to fault, cable ID, and far end device. What's more, its integrated RJ11, RJ45, and coax test ports support virtually any type of low-voltage cable testing with no need for awkward adapters. The end result is reduced test time and technician error. That makes high-quality installations more efficient than ever. Today's communications technicians have a lot more problems to deal with than just the cabling. They have to rule out a whole host of potentialcable and service issues before determining the cause of a connection problem. Is there telephone voltage? What's the polarity? Is there an Ethernet switch at the far end? Is PoE available? MicroScanner2 acknowledges this, giving technicians high power vision to verify today's most common voice, data, and video services. That means faster, more comprehensive troubleshooting.



- 1 Area of application: Verifies voice/data/video cable
-] General properties:
- 1 Display: Monochrome liquid crystal display
- 1 Housing: Plastic with show absorbing overmold
- Dimensions: 7.6 x 16.3 x 3.6 cm
- Weight: 363 g
- Battery: 2x AA-alkaline
- Life of battery: Up to 20 hours of typical use
- Package content: MicroScanner² Cable Verifier with main wiremap adapter
- IntelliTone Pro 200 kit
- Accessory soft pouch
- 1 Fluke Networks carry case
- Remote identifiers #2-7
- Shielded twisted pair RJ45 patch cord
- R.J11 patch cord
- 1 Clip-set RJ45 to 8 alligator clip bare wire adapter
- F Coax push on patch cord
- Technical properties:
- 1 Test Connectors: Twisted-pair: UTP, FTP, SSTP 8-pin modular jack accepts RJ45 and RJ11 Coax: F-connector for 75 Ω, 50 , 93 Ω cables
- IntelliTone Toning: Locates virtually any cable or wire pair with IntelliTone digital and analog toning
- VDV service detection: User-configurable NVP for twisted pair and coax
- Calibration: Determines actual NVP with known length of cable
- 1 Operating temperature: 0 °C to 45 °C

Package Content

- 1 1x MicroScanner² Cable Verifier with main wiremap adapter
- Remote identifiers #2-7
- 1 1x IntelliTone Pro 200 probe
- 1 1x shielded twisted-pair RJ45 patch cord
- 1 1x RJ11 patch cord
- 1 1x clip-set RJ45 to 8 alligator clip bare wire adapter
- 1 1x F Coax push on patch cord
- 1 1x accessory soft pouch
- 1 2x AA alkaline batteries. 1x 9V alkaline battery
- 1 1x MicroScanner2 Getting Started Guide, 1x MicroScanner2 Owners CD
- 1 1x IntelliTone Pro Getting Started Guide, 1xIntelliTone Pro owners CD
- 1 packaged in a deluxe Fluke Networks carry case

www.assmann.com 2/3

Fluke MicroScanner² Cable Verifier Professional Kit

ACT-MS2-KIT 4016032358893

→ Logistics	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	2,30	40,00	25,00	6,00	6000,00
Packaging Unit Inside	1	2,30	40,00	25,00	6,00	6000,00
Packaging Unit Single	1	2,30	40,00	25,00	6,00	6000,00
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00

→ Packaging type



www.assmann.com 3/3