

## Intellinet 561174 netwerk-switch Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

**Merk :** Intellinet

**Artikelcode:** 561174

**Productnaam :** 561174

Intellinet 561174. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 5. Full duplex. MAC-adrestabel: 2000 entries, Switchingcapaciteit: 10 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z. Netstekker: DC-in ingang. Power over Ethernet (PoE)



Poorten & interfaces		Design	
Aantal basis-switching RJ-45 Ethernet-poorten *	5	Certificering	FCC B, CE, IEC61000-4-2, IEC61000-4-4, IEC61000-4-5
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Energie	
Aantal Combo SFP-poorten	1	Vermogenstoevoer inclusief *	✓
Netstekker	DC-in ingang	AC-ingangsspanning	100 - 240 V
Netwerk		AC-ingangsfrequentie	50 - 60 Hz
Netwerkstandaard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z	Vermogensverbruik (max)	90 W
10G support *	✗	Power over Ethernet (PoE)	
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) *	✓
Full duplex	✓	Aantal Power over Ethernet plus (PoE +)-poorten	4
Datastroombeheer	✓	Vermogen per poort Power over Ethernet (PoE)	30 W
Auto MDI/MDI-X	✓	Totaal Power over Ethernet (PoE)-budget	80 W
Auto-negotiation	✓	Eisen aan de omgeving	
Data-uitwisseling		Bedrijfstemperatuur (T-T)	0 - 40 °C
Switchingcapaciteit *	10 Gbit/s	Temperatuur bij opslag	-20 - 70 °C
MAC-adrestabel *	2000 entries	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Store-and-forward	✓	Gewicht en omvang	
Jumbo Frames ondersteuning	✓	Breedte	160 mm
Jumbo frames	9000	Diepte	110 mm
Packet forwarding rate (1 Gbps)	1488000 pps	Hoogte	24 mm
Packet forwarding rate (100 Mbps)	148800 pps	Gewicht	950 g
Packet forwarding rate (10 Mbps)	14880 pps	Verpakking	
Design		Snelstartgids	✓
Kleur van het product	Zwart	Gebruikershandleiding	✓
Materiaal behuizing	Metaal	Logistieke gegevens	
LED-indicatoren	Activiteit, Link, Power over Ethernet (PoE), Stroom	Code geharmoniseerd systeem (HS) 85176990	



0766623561174



766623561174

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.