

Unleash performance beyond expectation




Solid State Drive | PCIe SSD 110S

Transcend's PCIe SSD 110S utilizes the PCI Express® Gen3 x4 interface supported by the latest NVMe™ standard, to unleash next-generation performance. The PCIe SSD 110S aims at high-end applications, such as digital audio/video production, gaming, and enterprise use, which require constant processing heavy workloads with no system lags or slowdowns of any kind. Powered by 3D NAND flash memory, the PCIe SSD 110S gives you not only fast transfer speeds but unmatched reliability.



PCIe Gen3 x4 interface and NVMe standard



3D NAND flash memory

- Space-saving M.2 Type 2280 form factor
- Engineered with LDPC (Low-Density Parity Check) coding to ensure data integrity
- Built-in SLC caching technology for exceptional transfer speeds
- $Engineered\ dynamic\ thermal\ throttling\ mechanism\ to\ prevent\ overheating\ while\ maintaining\ high\ performance$
- Supports Transcend SSD Scope software

Ordering Information

TS128GMTE110S 128GB TS256GMTE110S 256GB TS512GMTE110S 512GB



Dimensions (max.)	80.0mm × 22.0mm × 3.58mm (3.15" x 0.87" x 0.14")
Weight (max.)	8g (0.28 oz)
Interface	PCle Gen3 x4
Storage Media	TLC NAND Flash
Form Factor	M.2 Type 2280
Seq. Read/Write*	1,800MB/s, 1,500MB/s
Operating Voltage	DC 3.3V±5%
Operating Temperature	0°C(32°F) ~ 70°C(158°F)
Warranty	Five-year Limited Warranty

Some motherboards only provide PCle x2 connections for the M.2 slot, creating a bottleneck on even the fastest drives. Speed may vary due to host hardware, software, usage, and storage capacity.

^{*}Note: Performance is based on CrystalDiskMark v5.0.2.