

DATASHEET

RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, black

Article no.

K8104SW.20



Cat.6

5 Gbit

250 MHz

CCA

Description

Special features

Jacket material: LSZH

Cross section: 4 x 2 x **AWG24/7**

Cable diameter: 5.9mm

Type of grommet: moulded bend relief, slim version

General specifications

Category: Cat.6

Transmission: 5Gbit

Bandwidth: 250MHz

Assignment: According to TIA/EIA 568B

Conductor material: CCA

Connector: RJ45 unshielded, IEC-60603-7-5

Contacts: Gold plated

Latch protection: available

Cable structure: U/UTP

Flame retardance: IEC60332-1

Halogen free: IEC60754-2

Low smoke: IEC61034

General data

Category	6
Cable type	U/UTP
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Colour outer sheath	black
Anti-kink sleeve	plugged in
Locking lever	True
Colour anti-kink sleeve	black

This datasheet was created automatically on 09-07-2018 . Technical changes reserved.



DATASHEET

RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, black

Article no.

K8104SW.20

General data

Flame retardant version	True
Halogen free	True
Oil resistant (acc. EN 60811-2-1)	False
Cable construction	4x2
NVP value	- %
Pin assignment	1:1
AWG-size	24

Available variants

Article no.	Title	Length
K8104SW.0,5	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 0.5m, black	0.5 m
K8104SW.1	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 1m, black	1.0 m
K8104SW.1,5	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 1,5m, black	1.5 m
K8104SW.2	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 2m, black	2.0 m
K8104SW.3	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 3m, black	3.0 m
K8104SW.4	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 4m, black	4.0 m
K8104SW.5	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 5m, black	5.0 m
K8104SW.7,5	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 7,5m, black	7.5 m
K8104SW.10	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 10m, black	10.0 m
K8104SW.15	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 15m, black	15.0 m
K8104SW.20	RJ45 Patch cable U/UTP, Cat.6, LSZH, CCA, 20m, black	20.0 m

This datasheet was created automatically on 09-07-2018 . Technical changes reserved.

