

Intellinet 561259 netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk : Intellinet

Artikelcode: 561259

Productnaam : 561259

Intellinet 561259. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 16. Full duplex. MAC-adrestabel: 8192 entries, Switchingcapaciteit: 36 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE). Rack-montage



Beheerfuncties		Design	
Switch type *	Unmanaged	Certificering	FCC A, CE, RoHS
Poorten & interfaces		Prestatie	
Aantal basis-switching RJ-45 Ethernet-poorten *	16	Geluidsniveau	21,3 dB
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Mean time between failures (MTBF)	144000 uur
Aantal moduleslots SPF	2	Energie	
Netwerk		AC-ingangsspanning	100 - 240 V
Netwerkstandaard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	AC-ingangsfrequentie	50 - 60 Hz
10G support *	✗	Vermogensverbruik (max)	420 W
Koperen ethernetbekabelingstechnologie	100BASE-TX, 1000BASE-T	Stroomspanning bescherming	Overspanning, Overbelasting, Kortsluiting
Ondersteundende kabel types	Cat5, Cat5e	Power over Ethernet (PoE)	
Full duplex	✓	Power over Ethernet (PoE) *	✓
Datastroombeheer	✓	Aantal Power over Ethernet plus (PoE +)-poorten	16
Auto MDI/MDI-X	✓	Vermogen per poort Power over Ethernet (PoE)	30 W
Auto-sensing	✓	Totaal Power over Ethernet (PoE)-budget	370 W
Data-uitwisseling		Eisen aan de omgeving	
Switchingcapaciteit *	36 Gbit/s	Bedrijfstemperatuur (T-T)	0 - 45 °C
MAC-adrestabel *	8192 entries	Temperatuur bij opslag	-10 - 70 °C
Store-and-forward	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Packet forwarding rate (1 Gbps)	1488000 pps	Gewicht en omvang	
Packet forwarding rate (100 Mbps)	148800 pps	Breedte	441,1 mm
Packet forwarding rate (10 Mbps)	14880 pps	Diepte	204,3 mm
Packet buffergeheugen	0,5 MB	Hoogte	44 mm
Design		Gewicht	4 kg
Rack-montage *	✓	Verpakking	
Stapelbaar *	✗	Meegeleverde kabels	AC
Kleur van het product	Zwart	Gebruikershandleiding	✓
Materiaal behuizing	Metaal	Rekbevestigingspakket	✓
LED-indicatoren	Activiteit, Link, Power over Ethernet (PoE), Stroom, Snelheid	Logistieke gegevens	
Aantal ventilatoren	2 ventilator(en)	Code geharmoniseerd systeem (HS)	85176990



0766623561259



766623561259

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date