



LevelOne IGC-0101 netwerk media converter 1000 Mbit/s

Merk : LevelOne

Artikelcode: IGC-0101

Productnaam : IGC-0101

LevelOne IGC-0101. Maximale overdrachtsnelheid van gegevens: 1000 Mbit/s, Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet interface type: Gigabit Ethernet. Vezel-optische connector: SFP, Connectiviteitstechnologie: Bedraad. Mean time between failures (MTBF): 500000 uur. LED-indicatoren: Activiteit, Link, Stroom, Land van herkomst: Taiwan, Veiligheid: IEC EN60950-1. Ingangsspanning: 48 - 56 V, Stroomverbruik (typisch): 2 W, Totaal Power over Ethernet (PoE)-budget: 30 W



Netwerk		Energie	
Maximale overdrachtsnelheid van gegevens *	1000 Mbit/s	Stroomverbruik (typisch)	2 W
Netwerkstandaard	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE)	✓
Ethernet interface type	Gigabit Ethernet	Totaal Power over Ethernet (PoE)-budget	30 W
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Gewicht en omvang	
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Breedte	32 mm
Jumbo Frames ondersteuning	✓	Diepte	81,5 mm
Jumbo frames	9000	Hoogte	103,5 mm
Datastroombeheer	✓	Gewicht	135 g
Poorten & interfaces		Eisen aan de omgeving	
Connectiviteitstechnologie	Bedraad	Bedrijfstemperatuur (T-T)	-40 - 75 °C
Aantal Ethernet LAN (RJ-45)-poorten	1	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Fibre channel-poorten	1	Verpakking	
Vezel-optische connector *	SFP	Breedte verpakking	165 mm
Hoeveelheid Power over Ethernet (PoE) ports	1	Diepte verpakking	65 mm
		Hoogte verpakking	215 mm
		Gewicht verpakking	350 g
Prestatie		Inhoud van de verpakking	
Mean time between failures (MTBF)	500000 uur	Gebruikershandleiding	✓
Design		Logistieke gegevens	
Intern *	✗	Code geharmoniseerd systeem (HS)	85176990
LED-indicatoren	Activiteit, Link, Stroom	(Buitenste) hoofdverpakking breedte	350 mm
DIN rail bevestiging	✓	(Buitenste) hoofdverpakking lengte	240 mm
Land van herkomst	Taiwan	(Buitenste) hoofdverpakking hoogte	560 mm
Veiligheid	IEC EN60950-1	(Buitenste) hoofdverpakking brutogewicht	6,6 kg
Certificering	CE, FCC, VCCI, FCC Part 15 Subpart B Class A, CE EN 55022 Class A	Hoeveelheid per (buitenste) hoofdverpakking	16 stuk(s)
Energie			
Ingangsspanning	48 - 56 V		



4015867203910



4015867224236

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.