



## TP-Link TL-SG116 Unmanaged Gigabit Ethernet (10/100/1000) Zwart

**Merk :** TP-Link

**Artikelcode:** TL-SG116 V1

**Productnaam :** TL-SG116



TP-Link TL-SG116. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 16. Full duplex. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 32 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x



Beheerfuncties		Design	
Switch type *	Unmanaged	Certificering	CE, FCC ,RoHS
Quality of Service (QoS)	✓	<b>Prestatie</b>	
<b>Poorten &amp; interfaces</b>		Plug and play	✓
Aantal basis-switching RJ-45 Ethernet-poorten *	16	<b>Energie</b>	
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Stroombron *	DC
Aantal Gigabit Ethernet (koper)-poorten	16	Vermogenstoevoer inclusief *	✓
<b>Netwerk</b>		Stroom	1 A
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Ingangsspanning	12 V
10G support *	✗	Vermogensverbruik (max)	10 W
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	<b>Power over Ethernet (PoE)</b>	
Full duplex	✓	Power over Ethernet (PoE) *	✗
Datastroombeheer	✓	<b>Eisen aan de omgeving</b>	
Auto MDI/MDI-X	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
Auto-negotiation	✓	Temperatuur bij opslag	-40 - 70 °C
<b>Data-uitwisseling</b>		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	32 Gbit/s	Luchtvochtigheid bij opslag	5 - 90 procent
Verzending snelheid	23,8 Mpps	Warmtedissipatie	34,12 BTU/h
MAC-adrestabel *	8000 entries	<b>Gewicht en omvang</b>	
Store-and-forward	✓	Breedte	286 mm
Jumbo Frames ondersteuning	✓	Diepte	111,7 mm
Jumbo frames	10000	Hoogte	25,4 mm
Packet buffergeheugen	4,1 MB	<b>Verpakking</b>	
<b>Beveiliging</b>		Snelstartgids	✓
IGMP snooping	✓	Inclusief AC-adapter	✓
<b>Design</b>		Type verpakking	Doos
Rack-montage *	✗	Rubberen voetjes	✓
Kleur van het product	Zwart	Breedte verpakking	170 mm
		Diepte verpakking	412 mm
		Hoogte verpakking	70 mm

**Design**

Materiaal behuizing      Staal  
LED-indicatoren      ✓

**Verpakking**

Gewicht verpakking      1,33 kg

**Logistieke gegevens**

Code geharmoniseerd systeem (HS) 85176990



6935364084325



6935364084332



0845973084325



845973084325

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.