



Delock Adapter USB 2.0 Type-C male > 1 x Serial RS-232 RJ45 male 2.0 m black

Description

This USB 2.0 to RS-232 adapter by Delock is suitable for the console at CISCO routers, switches, access points and other compatible devices via PC or laptop.



Specification

- Connectors:
- 1 x USB 2.0 Type-C male
- 1 x Serial RS-232 RJ45 male
- Chipset: FTDI FT232RL
- Compatible with USB 3.0, USB 2.0, and USB 1.1 full speed 12 Mbps
- Data transfer rate up to 230.4 Kb/s
- Cable length incl. connectors: ca. 2.0 m
- · Suitable for various compatible CISCO devices


System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6
- PC or laptop with a free USB Type-C port

Package content

- USB 2.0 to 1 x Serial adapter
- User manual

Images



Item no. 63912

EAN: 4043619639120

Country of origin: China

Package: Poly bag







| General | |
|-------------------------------|------------------------|
| Function: | Plug & Play |
| Specification: | RS-232 |
| | USB 1.1 |
| | USB 3.0 |
| | USB 2.0 |
| Supported operating system: | Windows 7 32-bit |
| | Windows 7 64-bit |
| | Windows 8.1 32-bit |
| | Windows 8.1 64-bit |
| | Windows 10 32-bit |
| | Windows 10 64-bit |
| | Windows Server 2012 R2 |
| | Windows Server 2012 |
| | Windows Server 2016 |
| | ex Linux Kernel 2.6.x |
| | ex Mac OS 10.9 |
| Interface | |
| Connector 1: | 1 x USB Type-C™ male |
| Connector 2: | 1 x RJ45 plug |
| Technical characteristics | |
| Chipset: | FTDI FT232RL |
| Data transfer rate: | up to 230.4 Kb/s |
| FIFO: | 128 byte |
| | 256 Byte |
| Data transmission: | asynchronous |
| | full duplex |
| Physical characteristics | |
| Cable length incl. connector: | 2 m |
| Colour: | black |