LevelOne FVT-2202 netwerk media converter 100 Mbit/s Zwart

Merk : LevelOne

Artikelcode: FVT-2202

Productnaam : FVT-2202

LevelOne FVT-2202. Maximale overdrachtssnelheid van gegevens: 100 Mbit/s, Netwerkstandaard: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, Ethernet interface type: Fast Ethernet. Vezel-optische connector: SX, Connectiviteitstechnologie: Bedraad. Maximaal bereik: 20000 m, Vezelkabel diameters ondersteund: 8.3/125,9/125,10/125 µm. LED-indicatoren: Activiteit, Link, Stroom, Kleur van het product: Zwart, Land van herkomst: China. Ingangsspanning: 5 V, Stroom: 1 A

Netwerk	
Maximale overdrachtssnelheid van gegevens *	100 Mbit/s
Netwerkstandaard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Fast Ethernet
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX
Fiber ethernet cabling technologie	100BASE-FX
Datastroombeheer	✓
Auto MDI/MDI-X	✓
Auto-negotiation	✓
Store-and-forward	✓
Duplex systeem	Volledig, Half
Link Loss Carry Forward (LLCF) ondersteund	✓
Link Loss Return (LLR) ondersteund	✓
Ondersteundende kabel types	Cat5
Poorten & interfaces	
Connectiviteitstechnologie	Bedraad
Aantal Ethernet LAN (RJ-45)-poorten	1
Fibre channel-poorten	1
Vezel-optische connector *	SX
Prestatie	
Maximaal bereik *	20000 m
Golflengtemultiplexing (WDM)	✓
Vezelkabel diameters ondersteund	8.3/125,9/125,10/125 µm
Design	
Intern *	✗
LED-indicatoren	Activiteit, Link, Stroom
Kleur van het product	Zwart
Land van herkomst	China

Design	
Certificering	CE, FCC
Energie	
Ingangsspanning	5 V
Stroom	1 A
Gewicht en omvang	
Breedte	94 mm
Diepte	70 mm
Hoogte	25 mm
Gewicht	420 g
Eisen aan de omgeving	
Bedrijfstemperatuur (T-T)	-40 - 75 °C
Temperatuur bij opslag	-10 - 55 °C
Relatieve vochtigheid in bedrijf (V-V)	5 - 90 procent
Verpakking	
Breedte verpakking	235 mm
Diepte verpakking	125 mm
Hoogte verpakking	55 mm
Gewicht verpakking	914 g
Type verpakking	Blister
Inhoud van de verpakking	
Inclusief AC-adapter	✓
Snelle installatiehandleiding	✓
Logistieke gegevens	
Code geharmoniseerd systeem (HS)	85176990
(Buitenste) hoofdverpakking breedte	480 mm
(Buitenste) hoofdverpakking lengte	360 mm
(Buitenste) hoofdverpakking hoogte	390 mm
(Buitenste) hoofdverpakking brutogewicht	16,2 kg
Hoeveelheid per (buitenste) hoofdverpakking	36 stuk(s)

4015867200353

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAR-2024. Prints or copies of Information are only valid on the printed Publication date