

ZYXEL

Zyxel GS1005HP Unmanaged Gigabit Ethernet (10/100/1000)
Power over Ethernet (PoE) Zilver

Merk : Zyxel

Artikelcode: GS1005HP-EU0101F

Productnaam : GS1005HP

- Plug-and-play 5-poorts gigabit-switch met 4-poorts PoE+ connectiviteit
- 60 Watt aan totale output op 4 gigabit PoE+poorten
- Ondersteunt 802.3af/802.3at met een maximaal totaal vermogensbudget PoE+ van 30 Watt per poort
- LED-indicator voor max. vermogen Eenvoudig PoE budgetbeheer met LED-indicator voor max. vermogen
- Geavanceerde energiebesparingen op het werk en geruisloos ontwerp zonder ventilator
- Met een groter aantal slimme functies
- Robuuste metalen behuizing met de mogelijkheid van wandmontage

GS1005HP 5-Port GbE Unmanaged PoE Switch

Zyxel GS1005HP. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 5. Full duplex. MAC-adrestabel: 2048 entries, Switchingcapaciteit: 10 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE)



Beheerfuncties		Power over Ethernet (PoE)	
Switch type *	Unmanaged	Power over Ethernet (PoE) *	✓
Quality of Service (QoS)	✓	Aantal Power over Ethernet plus (PoE +)-poorten	4
Poorten & interfaces		Vermogen per poort Power over Ethernet (PoE)	30 W
Aantal basis-switching RJ-45 Ethernet-poorten *	5	Totaal Power over Ethernet (PoE)-budget	60 W
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Eisen aan de omgeving	
Netwerk		Bedrijfstemperatuur (T-T)	0 - 40 °C
Netwerkstandaard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Temperatuur bij opslag	-40 - 70 °C
10G support *	✗	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Full duplex	✓	Luchtvochtigheid bij opslag	10 - 90 procent
Datastroombeheer	✓	Gewicht en omvang	
Auto MDI/MDI-X	✓	Breedte	121 mm
Data-uitwisseling		Diepte	75 mm
Switchingcapaciteit *	10 Gbit/s	Hoogte	26 mm
MAC-adrestabel *	2048 entries	Gewicht	235 g
Jumbo Frames ondersteuning	✓	Verpakking	
Jumbo frames	9126	Snelstartgids	✓
Design		Inclusief AC-adapter	✓
Kleur van het product	Zilver	Breedte verpakking	210 mm
Certificering	CE, FCC, BSMI, EAC	Diepte verpakking	132 mm
Prestatie		Hoogte verpakking	78 mm
Buffergrootte	128 KB	Gewicht verpakking	834 g
Energie		Logistieke gegevens	
AC-ingangsspanning	100 - 240 V	Code geharmoniseerd systeem (HS) 85176990	
Spanning	55 V		
Output current	1,3 A		



4718937603923

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-SEP-2024. Prints or copies of Information are only valid on the printed Publication date