

D-Link DIS-200G-12PS netwerk-switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk : D-Link

Artikelcode: DIS-200G-12PS

Productnaam : DIS-200G-12PS

D-Link DIS-200G-12PS. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 10, Console port: RJ-45. Full duplex. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 24 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE... DC voltage input: 46 - 54 V. Power over Ethernet (PoE). Ophangstelsysteem voor aan de muur, Rack-montage



Beheerfuncties		Design	
Switch type *	Managed	Elektromagnetische compatibiliteit	CISPR 22, FCC Part 15B Class A
Switch-laag	L2		CE, FCC, BSMI EN 61000-4-2 ESD EN 61000-4-3 RS EN 61000-4-4 EFT EN 61000-4-5 EN 61000-4-6 CS EN 61000-4-8 IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6
Quality of Service (QoS)	✓	Certificering	
Web-gebaseerd management	✓		
Locatie-instellingen (CLI) configureren	✓		
System event log	✓		
Poorten & interfaces		Prestatie	
Aantal basis-switching RJ-45 Ethernet-poorten *	10	Mean time between failures (MTBF)	205689 uur
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Technische details	
Aantal Gigabit Ethernet (koper)-poorten	10	(Binnenste) verzendverpakking hoogte	25,2 cm
Aantal moduleslots SPF	2	(Binnenste) verzendverpakking breedte	37,2 cm
Console port	RJ-45	(Binnenste) verzendverpakking lengte	40,9 cm
Netwerk		Nettogewicht transportverpakking	11 kg
	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Producten per (binnenste) verzendverpakking	5 stuk(s)
Netwerkstandaard *		Pallet brutogewicht (lucht)	283,7 kg
10G support *	✗	Aantal dozen per pallet (lucht)	24 stuk(s)
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Aantal per pallet (lucht)	120 stuk(s)
Port mirroring	✓	Pallet brutolengte	110 cm
Full duplex	✓	Pallet brutobreedte	120 cm
Datastroombeheer	✓	Pallethoogte (lucht)	114,3 cm
Verbindingsaggregatie	✓	Pallet brutogewicht (zee)	496,4 kg
Broadcast stormbeheer	✓	Aantal dozen per pallet (zee)	42 stuk(s)
Auto MDI/MDI-X	✓	Producten per pallet (zee)	210 stuk(s)
Spanning tree protocol	✓	Pallethoogte (zee)	189,9 cm
Active Link-detectie	✓	(Binnenste) verzendverpakking gewicht	11,8 kg
VLAN=ondersteuning	✓	Energie	
Virtuele LAN-functies	Voice VLAN, Tagged VLAN, Port-based VLAN	DC voltage input	46 - 54 V
Aantal VLANs	4094	Vermogensverbruik (max)	260 W
		Spanningsbeveiliging	✓
		Overspanningsbeveiliging in voltage	6 kV
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓

Optische vezel		Power over Ethernet (PoE)	
Fiber ethernet cabling technologie	1000BASE-X	Hoeveelheid Power over Ethernet (PoE) ports	8
Data-uitwisseling		Vermogen per poort Power over Ethernet (PoE)	30 W
Switchingcapaciteit *	24 Gbit/s	Totaal Power over Ethernet (PoE)-budget	240 W
Verzending snelheid	17,85 Mpps	Eisen aan de omgeving	
MAC-adrestabel *	8000 entries	Bedrijfstemperatuur (T-T)	-40 - 65 °C
Store-and-forward	✓	Temperatuur bij opslag	-40 - 85 °C
Jumbo Frames ondersteuning	✓	Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
Jumbo frames	9216	Luchtvochtigheid bij opslag	0 - 95 procent
Beveiliging		Warmtedissipatie	887,16 BTU/h
DHCP-functies	DHCP client	Gewicht en omvang	
IGMP snooping	✓	Breedte	171,2 mm
Ondersteunde beveiligingsalgoritmen	802.1x RADIUS, SSL/TLS	Diepte	48 mm
Authenticatie	Poortgebaseerde authenticatie	Hoogte	210 mm
DoS aanval preventie	✓	Gewicht	2,5 kg
Authenticatie type	RADIUS	Verpakking	
Algoritmen wachtrijplanning	SPQ, Weighted Round Robin (WRR)	Breedte verpakking	217 mm
Multicast-functies		Diepte verpakking	355 mm
Multicast-ondersteuning	✓	Hoogte verpakking	76 mm
Protocollen		Gewicht verpakking	2,2 kg
Beheerprotocollen	SNMP v1/v2c/v3, SNMP, Telnet	Logistieke gegevens	
Design		Code geharmoniseerd systeem (HS)	85176990
Rack-montage *	✓		
Stapelbaar *	✗		
Kleur van het product	Zwart		
Materiaal behuizing	Metaal		
LED-indicatoren	✓		
Internationale veiligheidscode (IP)	IP30		
Ophangstelsel voor aan de muur	✓		
DIN rail bevestiging	✓		
Veiligheid	UL60950-1		



0790069433504



790069433504

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAR-2024. Prints or copies of Information are only valid on the printed Publication date