



LevelOne FVT-1106 netwerk media converter 100 Mbit/s 1550 nm Single-mode Zwart

Merk : LevelOne

Artikelcode: FVT-1106

Productnaam : FVT-1106

LevelOne FVT-1106. Maximale overdrachtssnelheid van gegevens: 100 Mbit/s, Converter input interface: 10Base-T, 100Base-TX, Converter output interface: 100Base-FX. Vezel-optische connector: SC, Connectiviteitstechnologie: Bedraad. Maximaal bereik: 120000 m, Golflengte: 1550 nm, Draad modus structuur: Single-mode. Kleur van het product: Zwart, Land van herkomst: China, Veiligheid: CE. Ingangsspanning: 5 V, Stroom: 1 A



Netwerk		Energie	
Maximale overdrachtssnelheid van gegevens *	100 Mbit/s	Ingangsspanning	5 V
Converter input interface	10Base-T, 100Base-TX	Stroom	1 A
Converter output interface	100Base-FX	Gewicht en omvang	
Netwerkstandaard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Breedte	94 mm
Ethernet interface type	Fast Ethernet	Diepte	71 mm
Ethernet LAN, data-overdrachtssnelheden	10,100 Mbit/s	Hoogte	26 mm
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX	Gewicht	200 g
Fiber ethernet cabling technologie	100BASE-FX	Eisen aan de omgeving	
Datastroombeheer	✓	Bedrijfstemperatuur (T-T)	0 - 50 °C
Auto MDI/MDI-X	✓	Temperatuur bij opslag	-20 - 70 °C
Auto-negotiation	✓	Relatieve vochtigheid in bedrijf (V-V)	5 - 90 procent
Store-and-forward	✓	Verpakking	
Duplex systeem	Volledig	Breedte verpakking	230 mm
Poorten & interfaces		Diepte verpakking	150 mm
Connectiviteitstechnologie	Bedraad	Hoogte verpakking	58 mm
Aantal Ethernet LAN (RJ-45)-poorten	1	Gewicht verpakking	300 g
Fibre channel-poorten	1	Type verpakking	Doos
Vezel-optische connector *	SC	Inhoud van de verpakking	
Aansluiting voor netstroomadapter	✓	Inclusief AC-adapter	✓
Prestatie		Snelle installatiehandleiding	✓
Maximaal bereik *	120000 m	Technische details	
Golflengte *	1550 nm	Duurzaamheidscertificaten	RoHS
Draad modus structuur	Single-mode	Logistieke gegevens	
Mean time between failures (MTBF)	100000 uur	Code geharmoniseerd systeem (HS)	85176990
Design		(Buitenste) hoofdverpakking breedte	440 mm
Intern *	✗	(Buitenste) hoofdverpakking lengte	420 mm
LED-indicatoren	✓	(Buitenste) hoofdverpakking hoogte	305 mm
Kleur van het product	Zwart	(Buitenste) hoofdverpakking brutogewicht	32 kg
Land van herkomst	China		
Veiligheid	CE		

Design		Logistieke gegevens	
--------	--	---------------------	--

Certificering	CE	Hoeveelheid per (buitenste) hoofdverpakking	40 stuk(s)
---------------	----	---	------------



4015867208083

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAR-2024. Prints or copies of Information are only valid on the printed Publication date