



## APC Easy-UPS SMV2000CAI - 6x C13, USB, 2000VA

**Merk :** APC

**Artikelcode:** SMV2000CAI

**Productnaam :** APC Easy-UPS SMV2000CAI - 6x C13, USB, 2000VA

APC Easy-UPS SMV2000CAI - 6x C13, USB, 2000VA

APC Easy-UPS SMV2000CAI - 6x C13, USB, 2000VA. UPS-topologie: Line-interactive, Output power capacity: 2 kVA, Uitgangsvermogen: 1400 W. Stopcontacttypes: IEC 320, Aantal AC uitgangen: 6 AC-uitgang(en). Batterijtechnologie: Sealed Lead Acid (VRLA), Batterij capaciteit: 7 Ah, Accu/Batterij voltage: 12 V. Vormfactor: Tower, Kleur van het product: Zwart, Type beeldscherm: LCD. Meegeleverde kabels: USB-kabel



| Kenmerken                          |                                                                                       | Accu/Batterij                          |                |
|------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|----------------|
| UPS-topologie *                    | Line-interactive                                                                      | Ondersteund aantal accu's/batterijen   | 4              |
| Output power capacity *            | 2 kVA                                                                                 | Acculevensduur (max)                   | 5 jaar         |
| Uitgangsvermogen *                 | 1400 W                                                                                | Accu/Batterij oplaadtijd               | 4 uur          |
| Golfvorm *                         | Sinus                                                                                 | Koude start                            | ✓              |
| Ingang operation voltage (min) *   | 157 V                                                                                 | <b>Design</b>                          |                |
| Ingang operation voltage (max) *   | 303 V                                                                                 | Vormfactor *                           | Tower          |
| Frequentie *                       | 45/65 Hz                                                                              | Kleur van het product *                | Zwart          |
| Uitgang operation voltage (min)    | 230 V                                                                                 | Type beeldscherm                       | LCD            |
| Uitgang operation voltage (max)    | 230 V                                                                                 | LED-indicatoren                        | ✓              |
| Output frequentie                  | 50/60 Hz                                                                              | Internationale veiligheidscode (IP)    | IP20           |
| Uitgangsspanningsregeling          | -1 - 1 procent                                                                        | <b>Eisen aan de omgeving</b>           |                |
| Automatic Voltage Regulation (AVR) | ✓                                                                                     | Bedrijfstemperatuur (T-T)              | 0 - 40 °C      |
| Stroom (max.)                      | 20 A                                                                                  | Temperatuur bij opslag                 | -10 - 40 °C    |
| Crest factor                       | 3:1                                                                                   | Relatieve vochtigheid in bedrijf (V-V) | 0 - 95 procent |
| Geluidsniveau                      | 45 dB                                                                                 | Luchtvochtigheid bij opslag            | 0 - 95 procent |
| Stroomspanning bescherming         | Overbelasting, Kortsluiting                                                           | Hoogte, in bedrijf                     | 0 - 3000 m     |
| Geluidsalarm(en)                   | ✓                                                                                     | <b>Inhoud van de verpakking</b>        |                |
| Hoorbare alarmstanden              | Alarm bij werking op batterij, Alarm bij laag batterijniveau, Alarm bij overbelasting | Meegeleverde kabels                    | USB-kabel      |
| <b>Poorten &amp; interfaces</b>    |                                                                                       | Gebruikershandleiding                  | ✓              |
| Stopcontacttypes                   | IEC 320                                                                               | <b>Gewicht en omvang</b>               |                |
| Aantal AC uitgangen                | 6 AC-uitgang(en)                                                                      | Breedte                                | 180 mm         |
| USB-poort                          | ✓                                                                                     | Diepte                                 | 455 mm         |
| <b>Accu/Batterij</b>               |                                                                                       | Hoogte                                 | 240 mm         |
| Batterijtechnologie                | Sealed Lead Acid (VRLA)                                                               | Gewicht                                | 23,5 kg        |
| Batterij capaciteit                | 7 Ah                                                                                  | Batterijbreedte                        | 32,6 cm        |
| Accu/Batterij voltage              | 12 V                                                                                  | Batterijdiepte                         | 60,1 cm        |
|                                    |                                                                                       | Batterijhoogte                         | 41 cm          |
|                                    |                                                                                       | Gewicht batterij                       | 26,9 kg        |

**Logistieke gegevens**

Code geharmoniseerd systeem (HS) 85078000



0731304346548



731304346548

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.