

D-Link DGS-1250-28XMP netwerk-switch Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk : D-Link

Artikelcode: DGS-1250-28XMP

Productnaam : DGS-1250-28XMP



D-Link DGS-1250-28XMP. Switch type: Managed, Switch-laag: L3. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 24, Console port: RJ-45. Full duplex. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 128 Gbit/s. Netwerkstandaard: IEEE 802.3af, IEEE 802.3at. Power over Ethernet (PoE). Rack-montage



Beheerfuncties		Prestatie	
Switch type *	Managed	Type geheugen	DDR3-SDRAM
Switch-laag	L3	Intern geheugen	2048 MB
Quality of Service (QoS)	✓	Flash memory	64 MB
Web-gebaseerd management	✓	Geluidsniveau	50,8 dB
ARP-inspectie	✓	Upgraden van firmware mogelijk	✓
Locatie-instellingen (CLI) configureren	✓	Mean time between failures (MTBF)	463430,16 uur
System event log	✓	Technische details	
	RFC2893, RFC4213, RFC4291, RFC2464, RFC2462, RFC4862, RFC2461, RFC4861, RFC2573, RFC1321, RFC2284, RFC2865, RFC2716, RFC3580, RFC826, RFC2463, RFC4443, RFC792, RFC793, RFC768, RFC791, RFC2389, RFC4113, RFC4022, RFC2618, RFC2674, RFC1398, RFC1643, RFC1650, RFC2358, RFC2665, RFC2021, RFC271, RFC1757, RFC2819, RFC1442, RFC1901, RFC1902, RFC1903, RFC1904, RFC1905, RFC1906, RFC1907, RFC1908, RFC2578, RFC3418, RFC2573, RFC2575, RFC2576, RFC1212, RFC1213, RFC1215, RFC1493, RFC1157, RFC2620,	(Binnenste) verzendverpakking hoogte	42,8 cm
MIB-ondersteuning		(Binnenste) verzendverpakking breedte	47,8 cm
		(Binnenste) verzendverpakking lengte	58,5 cm
		Nettogewicht transportverpakking	19,3 kg
		Producten per (binnenste) verzendverpakking	5 stuk(s)
		Pallet brutogewicht (lucht)	426 kg
		Aantal dozen per pallet (lucht)	16 stuk(s)
		Aantal per pallet (lucht)	80 stuk(s)
		Pallet brutolengte	110 cm
		Pallet brutobreedte	120 cm
		Pallethoogte (lucht)	184,7 cm
		Pallet brutogewicht (zee)	426 kg
		Aantal dozen per pallet (zee)	16 stuk(s)
		Producten per pallet (zee)	80 stuk(s)
		Pallethoogte (zee)	184,7 cm
		(Binnenste) verzendverpakking gewicht	25,5 kg
Poorten & interfaces		Energie	
Aantal basis-switching RJ-45 Ethernet-poorten *	24	Vermogenstoevoer inclusief *	✓
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	AC-ingangsspanning	100 - 240 V
Aantal moduleslots SPF+	4	AC-ingangsfrequentie	50 - 60 Hz
Console port	RJ-45	Vermogensverbruik (max)	455,1 W
Netwerk		Power over Ethernet (PoE)	
Netwerkstandaard *	IEEE 802.3af, IEEE 802.3at	Power over Ethernet (PoE) *	✓
10G support *	✓		
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T		
Ondersteundende kabel types	Cat5, Cat5e		
Port mirroring	✓		

Netwerk		Power over Ethernet (PoE)	
Full duplex	✓	Hoeveelheid Power over Ethernet (PoE) ports	24
Datastroombeheer	✓	Vermogen per poort Power over Ethernet (PoE)	15,4 W
Verbindingsaggregatie	✓	Totaal Power over Ethernet (PoE)-budget	370 W
Broadcast stormbeheer	✓	Eisen aan de omgeving	
Auto MDI/MDI-X	✓	Bedrijfstemperatuur (T-T)	-5 - 50 °C
Spanning tree protocol	✓	Temperatuur bij opslag	-20 - 70 °C
Head-of-line (HOL) blocking	✓	Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
VLAN=ondersteuning	✓	Luchtvochtigheid bij opslag	0 - 95 procent
Virtuele LAN-functies	Voice VLAN	Warmtedissipatie	1551,891 BTU/h
Aantal VLANs	4094	Gewicht en omvang	
Optische vezel		Breedte	440 mm
Fiber ethernet cabling technologie	100BASE-FX, 1000BASE-LHX, 1000BASE-X, 1000BASE-LX, 1000BASE-SX, 1000BASE-ZX	Diepte	250 mm
Data-uitwisseling		Hoogte	44 mm
Switchingcapaciteit *	128 Gbit/s	Gewicht	3,46 kg
Verzending snelheid	95,24 Mpps	Verpakking	
MAC-adrestabel *	16000 entries	Breedte verpakking	393 mm
Store-and-forward	✓	Diepte verpakking	563 mm
Statische route	✓	Hoogte verpakking	89 mm
Aantal statische routes	124	Gewicht verpakking	4,76 kg
Jumbo Frames ondersteuning	✓	Logistieke gegevens	
Jumbo frames	12000	Code geharmoniseerd systeem (HS)	85176990
Packet buffergeheugen	12 MB		
Beveiliging			
DHCP-functies	DHCP server, DHCP snooping		
Access Control List (ACL)	✓		
Regels voor toegangscontrolelijst (ACL)	768		
IGMP snooping	✓		
Ondersteunde beveiligingsalgoritmen	EAP, LEAP, MD5, PEAP, SSH, SSL/TLS, TTLS		
Bescherming lus	✓		
IP-MAC-Port binding	✓		
Algoritmen wachtrijplanning	Weighted Round Robin (WRR)		
Multicast-functies			
Multicast-ondersteuning	✓		
Design			
Rack-montage *	✓		
Kleur van het product	Zwart		
LED-indicatoren	Activiteit, Link, Stroom, Snelheid		
Elektromagnetische compatibiliteit	CE A, VCCI A, FCC A, IC, BSMI		
Certificering	CB, UL, BSMI, CCC		



0790069443008



790069443008

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAR-2024. Prints or copies of Information are only valid on the printed Publication date