

StarTech.com 7m LC/UPC naar LC/UPC OM4 Multimode Glasvezel Netwerkkabel, 50/125µm LOMMF/VCSEL Zipcord Fiber, 100G Netwerken, Low Insertion Loss, LSZH Fiber Patch Kabel

Merk : StarTech.com

Artikelcode: 450FBLCLC7



Productnaam : 7m LC/UPC naar LC/UPC OM4 Multimode Glasvezel Netwerkkabel, 50/125µm LOMMF/VCSEL Zipcord Fiber, 100G Netwerken, Low Insertion Loss, LSZH Fiber Patch Kabel

StarTech.com 7m LC/UPC naar LC/UPC OM4 Multimode Glasvezel Netwerkkabel, 50/125µm LOMMF/VCSEL Zipcord Fiber, 100G Netwerken, Low Insertion Loss, LSZH Fiber Patch Kabel (450FBLCLC7)

StarTech.com 7m LC/UPC naar LC/UPC OM4 Multimode Glasvezel Netwerkkabel, 50/125µm LOMMF/VCSEL Zipcord Fiber, 100G Netwerken, Low Insertion Loss, LSZH Fiber Patch Kabel:

LSZH Mantel | Aramidevezel Huls | Ideaal for SANs, data servers, SFP+

The StarTech.com Advantage
StarTech.com 7m LC/UPC naar LC/UPC OM4 Multimode Glasvezel Netwerkkabel, 50/125µm LOMMF/VCSEL Zipcord Fiber, 100G Netwerken, Low Insertion Loss, LSZH Fiber Patch Kabel. Snoerlengte: 7 m, Type glasvezel: OM4, Aansluiting 1: LC, Aansluiting 2: LC, Kern diameter: 50 µm, Full duplex



Kenmerken		Eisen aan de omgeving	
Snoerlengte *	7 m	Temperatuur bij opslag	-20 - 60 °C
Type glasvezel	OM4	Gewicht en omvang	
Aansluiting 1 *	LC	Gewicht	94 g
Aansluiting 2 *	LC	Verpakking	
Aansluiting 1 type *	Mannelijk	Aantal per verpakking	1 stuk(s)
Aansluiting 2 type *	Mannelijk	Breedte verpakking	220 mm
Kleur van het product *	Aqua-kleur	Diepte verpakking	200 mm
Full duplex	✓	Hoogte verpakking	15 mm
Kern diameter	50 µm	Gewicht verpakking	104 g
Bekleding diameter	125 µm	Logistieke gegevens	
Draad modus structuur	Multimode	(Buitenste) hoofdverpakking breedte	410 mm
Ondersteunde golflengten	850 nm	Code geharmoniseerd systeem (HS)	85447000
Overdrachtssnelheid	100 Gbit/s	(Buitenste) hoofdverpakking lengte	410 mm
Materiaal buitenmantel *	Halogeenvrij	(Buitenste) hoofdverpakking hoogte	450 mm
Technische details		Hoeveelheid per (buitenste) hoofdverpakking	120 stuk(s)
Naleving van duurzaamheid	✓		
Bevat geen	Halogeen		
Certificaten van naleving	RoHS, CE		
Eisen aan de omgeving			
Bedrijfstemperatuur (T-T)	-20 - 60 °C		



0065030881821



065030881821

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-SEP-2024. Prints or copies of Information are only valid on the printed Publication date