



## TP-Link LS1005G Unmanaged Gigabit Ethernet (10/100/1000) Zwart

**Merk :** TP-Link

**Artikelcode:** LS1005G V1

**Productnaam :** LS1005G



TP-Link LS1005G. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 5. MAC-adrestabel: 2000 entries, Switchingcapaciteit: 10 Gbit/s. Netwerkstandaard: IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Ophangstelsysteem voor aan de muur



| Beheerfuncties                                  |                                       | Design                                    |                 |
|---|---------------------------------------|---|-----------------|
| Switch type *                                   | Unmanaged                             | Certificering                             | CE, FCC, RoHS   |
| Poorten & interfaces                            |                                       | Energie                                   |                 |
| Aantal basis-switching RJ-45 Ethernet-poorten * | 5                                     | Stroombron *                              | DC              |
| Type basis-switching RJ-45 Ethernet-poorten *   | Gigabit Ethernet (10/100/1000)        | Vermogenstoevoer inclusief *              | ✓               |
| Aantal Gigabit Ethernet (koper)-poorten         | 5                                     | Stroom                                    | 0.6 A           |
|   |                                       | Ingangsspanning                           | 5 V             |
|   |                                       | Vermogensverbruik (max)                   | 3,7 W           |
| Netwerk   |                                       | Power over Ethernet (PoE)                 |                 |
| Netwerkstandaard *                              | IEEE 802.3i, IEEE 802.3u, IEEE 802.3x | Power over Ethernet (PoE) *               | ✗               |
| 10G support *                                   | ✗                                     | Eisen aan de omgeving                     |                 |
| Datastroombeheer                                | ✓                                     | Bedrijfstemperatuur (T-T)                 | 0 - 40 °C       |
| Auto MDI/MDI-X                                  | ✓                                     | Temperatuur bij opslag                    | -40 - 60 °C     |
| Auto-negotiation                                | ✓                                     | Relatieve vochtigheid in bedrijf (V-V)    | 10 - 90 procent |
| Data-uitwisseling                               |                                       | Luchtvochtigheid bij opslag               | 5 - 90 procent  |
| Switchingcapaciteit *                           | 10 Gbit/s                             | Warmtedissipatie                          | 12,617 BTU/h    |
| Verzending snelheid                             | 7,4 Mpps                              | Gewicht en omvang                         |                 |
| MAC-adrestabel *                                | 2000 entries                          | Breedte                                   | 90 mm           |
| Store-and-forward                               | ✓                                     | Diepte                                    | 72 mm           |
| Jumbo Frames ondersteuning                      | ✓                                     | Hoogte                                    | 23 mm           |
| Jumbo frames                                    | 16000                                 | Verpakking                                |                 |
| Packet buffergeheugen                           | 1,5 MB                                | Snelstartgids                             | ✓               |
| Design  |                                       | Type verpakking                           | Doos            |
| Rack-montage *                                  | ✗                                     | Breedte verpakking                        | 91 mm           |
| Kleur van het product                           | Zwart                                 | Diepte verpakking                         | 94 mm           |
| Materiaal behuizing                             | Kunststof                             | Hoogte verpakking                         | 84 mm           |
| LED-indicatoren                                 | Activiteit, Link, Stroom              | Gewicht verpakking                        | 180 g           |
| Ophangstelsysteem voor aan de muur              | ✓                                     | Logistieke gegevens                       |                 |
|   |                                       | Code geharmoniseerd systeem (HS) 85176990 |                 |



6935364085469



6935364085506

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.