



TP-Link LS1008G Unmanaged Gigabit Ethernet (10/100/1000) Zwart

Merk : TP-Link

Artikelcode: LS1008G V1

Productnaam : LS1008G



- 8x 10/100/1000 Mbps RJ45-poorten met Auto-Negotiation en ondersteuning van Auto-MDI/MDIX
- Met Green Ethernet-technologie bespaar je stroom
- IEEE 802.3x-datatransportbesturing zorgt voor een betrouwbare gegevensoverdracht
- Kunststof behuizing, geschikt voor desktop- of wandmontage
- Plug-and-play: geen configuratie nodig
- Ventilatorloos ontwerp en dus erg stil

LS1008G 8-poorts 10/100/1000 Mbps Desktopswitch

TP-Link LS1008G. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 8. MAC-adrestabel: 4000 entries, Switchingcapaciteit: 16 Gbit/s. Netwerkstandaard: IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Netstekker: DC-in ingang. Ophangstelsysteem voor aan de muur



Beheerfuncties		Design	
Switch type *	Unmanaged	Certificering	CE, FCC, RoHS
Poorten & interfaces		Energie	
Aantal basis-switching RJ-45 Ethernet-poorten *	8	Stroombron *	DC
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Vermogenstoevoer inclusief *	✓
Aantal Gigabit Ethernet (koper)-poorten	8	Stroom	0.6 A
Netstekker	DC-in ingang	Ingangsspanning	5 V
Netwerk		Vermogensverbruik (max)	3,9 W
Netwerkstandaard *	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✗
Datastroombeheer	✓	Eisen aan de omgeving	
Auto MDI/MDI-X	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
Auto-negotiation	✓	Temperatuur bij opslag	-40 - 60 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	16 Gbit/s	Luchtvochtigheid bij opslag	5 - 90 procent
Verzending snelheid	11,9 Mpps	Warmte-dissipatie	13,299 BTU/h
MAC-adrestabel *	4000 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	127 mm
Jumbo Frames ondersteuning	✓	Diepte	66,5 mm
Jumbo frames	16000	Hoogte	23 mm
Packet buffergeheugen	1,5 MB	Verpakking	
Design		Snelstartgids	✓
Kleur van het product	Zwart	Type verpakking	Doos
Materiaal behuizing	Kunststof	Breedte verpakking	90 mm
LED-indicatoren	Activiteit, Link, Stroom	Diepte verpakking	131 mm
Ophangstelsysteem voor aan de muur	✓	Hoogte verpakking	84 mm
		Gewicht verpakking	220 g
Logistieke gegevens			
Code geharmoniseerd systeem (HS) 85176990			



6935364085476



6935364085513

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-SEP-2024. Prints or copies of Information are only valid on the printed Publication date