## Zyxel GS1350-26HP-EU0101F netwerk-switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grijs

Merk: Zyxel Artikelcode: GS1350-26HP-EU0101F

Productnaam: GS1350-26HP-EU0101F

- Met NebulaFlex Pro kunnen gebruikers in combinatie met Pro Pack voor 1 jaar flexibel wisselen tussen standalone-beheer en Nebula-cloudbeheer
- Standalone: Eenvoudig beheer en gemakkelijke installatie met de webgebaseerde GUI
- Nebula Cloud: Nebula Cloud maakt eenvoudige implementatie en flexibel netwerkbeheer mogelijk zonder dat daarvoor software of een controller moet worden geïnstalleerd
- Groot stroombudget

GS1350-26HP, 26 Port managed CCTV PoE switch, long range, 375W

Zyxel GS1350-26HP-EU0101F. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 24. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 52 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ad, IEEE 802.3af, IEEE.... Power over Ethernet (PoE). Rack-montage





Switch type * Managed Multicast support				
Switch layer  Web-based management  Configuring Location Settings (CLI)  System event log  RFC 1066, RFC 1213, 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011, 2012, 2013, RFC 2233, RFC 2674, RFC 2819, 2925, RFC 3621, RFC 4923, RFC 4922, RFC 4113  Basic switching RJ-45 Ethernet ports quantity  Basic switching RJ-45 Ethernet ports by type  Network  REEE 802.1D, IEEE 802.1D, IEEE 802.1D, IEEE 802.3A, IEEE 802.	Management features		Multicast features	
Web-based management Web-based management V	Switch type *	Managed	Multicast support	✓
Rack mounting *	Switch layer	RFC 1066, RFC 1213, 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011, 2012, 2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819, 2925, RFC 3621, RFC 4293, RFC 4292,	Design	
Configuring Location Settings (CLI)  System event log  Apperature of the support	Web-based management		Rack mounting *	/
System event log  RFC 1066, RFC 1213, 1157, RFC 1493, RFC 1643, RFC 1757, RFC 1213, 1157, RFC 2011, 2012, 2013, RFC 2233, RFC 2338, RFC 2674, RFC 2819, 2925, RFC 3621, RFC 4293, RFC 4292, RFC 4022, RFC 4113  Ports & interfaces  Basic switching RJ-45 Ethernet ports 4 24  Basic switching RJ-45 Ethernet ports 4 292  Combo SFP ports quantity  Network  REE 802.1D, IEEE 802.1ab, IEEE 802.3, IEEE 802.3a, IEEE 80	Configuring Location Settings (CLI)		<u>.</u>	
MIB support    1493, RFC 1643, RFC 2777, RFC 2011, 2012, 2013, RFC 2233, RFC 2338, RFC 2374, RFC 2819, 2925, RFC 3621, RFC 4292, RFC 4022, RFC 4113   Power	System event log		LED indicators	,
Ac input voltage Ac input frequency Ac input frequ	MIB support		Electromagnetic compatibility	CE, FCC, C-Tick, A; BSMI CNS13438
RFC 3621, RFC 4293, RFC 4292, RFC 4113  Ports & interfaces  Basic switching RJ-45 Ethernet ports quantity*  Basic switching RJ-45 Ethernet ports type *  Combo SFP ports quantity  Network  BEEE 802.1D, IEEE 802.1ab, IEEE 802.3at, IEEE 802.3a			Performance	
Ports & interfaces  Basic switching RJ-45 Ethernet ports quantity*  Basic switching RJ-45 Ethernet ports bype *  Combo SFP ports quantity  Network  Networking standards *  Copper ethernet cabling technology  100 - 240 V  AC input voltage AC input frequency AC input voltage AC input voltag			Noise level	40.1 dB
Basic switching RJ-45 Ethernet ports quantity *  Basic switching RJ-45 Ethernet ports type *  Combo SFP ports quantity 2  Network  Networking standards *  IEEE 802.1D, IEEE 802.1ab, IEEE 802.3, IEEE 802.3ad, IEEE			Firmware upgradeable	<b>✓</b>
Basic switching RJ-45 Ethernet ports type * Combo SFP ports quantity  Network  Networking standards *  IEEE 802.1D, IEEE 802.1ab, IEEE 802.3af, IEEE 802.3a	Ports & interfaces		Mean time between failures (MTBF)	888495 h
AC input frequency 50 - 60 Hz	Basic switching RJ-45 Ethernet ports quantity *	24	Power	
Combo SFP ports quantity  2  Power consumption (max)  448.9 W  Power over Ethernet (PoE)  Network  Networking standards *  IEEE 802.1D, IEEE 802.1ab, IEEE 802.3a, IEEE 802.1ab, IEEE 802.3af, IEEE 80	Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)		
Network  Networking standards *    IEEE 802.1D, IEEE 802.1ab, IEEE 802.3at, IEEE 802.1ab, IEEE 802.3at, IEEE 802.3	type *		' '	
Networking standards *    IEEE 802.1D, IEEE 802.1ab, IEEE 802.3, IEEE 802.1w, IEEE 802.3, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3x, IEEE 802.3x	,	2	, , ,	448.9 W
Networking standards *     802.1p, IEEE 802.3w, IEEE 802.3, IEEE 802.3, IEEE 802.3at,	Network		Power over Ethernet (PoE)	
Networking standards * IEEE 802.3ad, IEEE 802.3af, IEEE 802.3af, IEEE 802.3at, IEEE 80	Networking standards *	* 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) *	✓
IEEE 802.3z  10G support *  Copper ethernet cabling technology  Total Power over Ethernet (PoE) budget  Total Power over Ethernet (PoE) budget  Operational conditions  Operating temperature (T-T) -20 - 50 °C				24
Copper ethernet cabling technology T 10BASE-TX, 100BASE-TX, 1000BASE-TX Operational conditions  Operational conditions  Operating temperature (T-T) -20 - 50 °C	100		, ,	375 W
Copper ethernet cabling technology T T Operating temperature (T-T) -20 - 50 °C	10G support *	10RASE_T 100RASE_TY 1000RASE_	Operational conditions	
The state of the s	Copper ethernet cabling technology		•	-20 - 50 °C
the state of the s	Port mirroring	✓		
Flow control support   Operating relative humidity (H-H) 5 - 95%	Flow control support	<b>✓</b>	· · · ·	5 - 95%
Character relative boundary (ULI) 5 OF 0/	Broadcast storm control	✓	Storage relative humidity (H-H)	5 - 95%
Rate limiting Heat dissipation 1530.75 BTU/h	Rate limiting	✓	Heat dissipation	1530.75 BTU/h

Network		Weight & dimensions	
Spanning tree protocol VLAN support Virtual LAN features	✓ ✓ MAC address-based VLAN, Port- based VLAN	Width Depth Height Weight	441 mm 270 mm 44 mm 3.58 kg
Number of VLANs	256	Packaging content	
Optical fiber		Cables included	AC
Fiber ethernet cabling technology	1000BASE-X	Rack mount kit	✓
Data transmission		Logistics data	
Switching capacity * Forwarding rate MAC address table * Packet buffer memory	52 Gbit/s 38.7 Mpps 8000 entries 0.525 MB	Harmonized System (HS) code	85176990
Security			
DHCP features	DHCP client, DHCP relay, DHCP snooping		
IGMP snooping	✓		
IGMP proxy	✓		
Security algorithms	SNMP, SNMPv3, SSH, SSL/TLS		
Loop protection	✓		
Queue scheduling algorithms	SPQ, WFQ, Weighted Round Robin (WRR)		





4718937604463

0760559126353



760559126353

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.