

## NETGEAR GS316PP Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart



**Merk :** NETGEAR

**Artikelcode:** GS316PP-100EUS

**Productnaam :** GS316PP

NETGEAR GS316PP. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 16. Full duplex. MAC-adrestabel: 4000 entries, Switchingcapaciteit: 32 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE.... DC voltage input: 54 V. Netstekker: DC-in ingang. Power over Ethernet (PoE). Ophangstelsysteem voor aan de muur, Rack-montage

Beheerfuncties		Design	
Switch type *	Unmanaged	Ophangstelsysteem voor aan de muur	✓
Quality of Service (QoS)	✓	Certificering	CE, FCC Part A, IC A, RCM, VCCI, BSMI, KC, CB, CE LVD
Poorten & interfaces		Prestatie	
Aantal basis-switching RJ-45 Ethernet-poorten *	16	Mean time between failures (MTBF)	2362192 uur
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Energie	
Netstekker	DC-in ingang	DC voltage input	54 V
Netwerk		Stroom	3.7 A
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Vermogensverbruik (max)	195,9 W
10G support *	✗	Power over Ethernet (PoE)	
Full duplex	✓	Power over Ethernet (PoE) *	✓
Datastroombeheer	✓	Aantal Power over Ethernet plus (PoE +)-poorten	16
Auto MDI/MDI-X	✓	Vermogen per poort Power over Ethernet (PoE)	30 W
Auto-sensing	✓	Totaal Power over Ethernet (PoE)-budget	183 W
Auto-negotiation	✓	Eisen aan de omgeving	
Data-uitwisseling		Bedrijfstemperatuur (T-T)	0 - 40 °C
Switchingcapaciteit *	32 Gbit/s	Temperatuur bij opslag	-20 - 70 °C
MAC-adrestabel *	4000 entries	Relatieve vochtigheid in bedrijf (V-V)	0 - 90 procent
Latentie (1 Gbps)	3,7 µs	Hoogte, in bedrijf	0 - 3000 m
Jumbo Frames ondersteuning	✓	Warmtedissipatie	669,9 BTU/h
Jumbo frames	9216	Gewicht en omvang	
Packet forwarding rate (1 Gbps)	1448000 pps	Breedte	286 mm
Packet buffergeheugen	1 MB	Diepte	102 mm
Beveiliging		Hoogte	27 mm
Algoritmen wachtrijplanning	Weighted Round Robin (WRR)	Gewicht	880 g
Design		Logistieke gegevens	
Rack-montage *	✓	Code geharmoniseerd systeem (HS)	85176990
Kleur van het product	Zwart		
Materiaal behuizing	Metaal		
LED-indicatoren	Activiteit, Link, Power over Ethernet (PoE), Stroom, Snelheid		



0606449146912



606449146912

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.