



## TP-Link TL-SG1210P Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grijs

**Merk :** TP-Link

**Artikelcode:** TL-SG1210P V1

**Productnaam :** TL-SG1210P



TP-Link TL-SG1210P. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 9. MAC-adrestabel: 4000 entries, Switchingcapaciteit: 20 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x. DC voltage input: 53.5 V. Power over Ethernet (PoE)



<b>Beheerfuncties</b>		<b>Design</b>	
Switch type *	Unmanaged	Certificering	CE, FCC, RoHS
Quality of Service (QoS)	✓	<b>Prestatie</b>	
<b>Poorten &amp; interfaces</b>		Fanloos	✓
Aantal basis-switching RJ-45 Ethernet-poorten *	9	<b>Energie</b>	
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Stroombron *	DC
Aantal Gigabit Ethernet (koper)-poorten	9	Vermogenstoevoer inclusief *	✓
Aantal moduleslots SPF	1	DC voltage input	53.5 V
<b>Netwerk</b>		Stroom	1.31 A
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x	Vermogensverbruik (max)	78,13 W
10G support *	✗	<b>Power over Ethernet (PoE)</b>	
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) *	✓
Auto MDI/MDI-X	✓	Aantal Power over Ethernet plus (PoE +)-poorten	8
Auto-negotiation	✓	Totaal Power over Ethernet (PoE)-budget	63 W
MAC-adres zelflerende functie	✓	<b>Eisen aan de omgeving</b>	
MAC-adres zelfverouderende functie	✓	Bedrijfstemperatuur (T-T)	0 - 50 °C
<b>Optische vezel</b>		Temperatuur bij opslag	-40 - 70 °C
Fiber ethernet cabling technologie	1000BASE-X	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Fiber type	Single-mode	Luchtvochtigheid bij opslag	5 - 90 procent
<b>Data-uitwisseling</b>		Warmtedissipatie	266,42 BTU/h
Switchingcapaciteit *	20 Gbit/s	<b>Gewicht en omvang</b>	
MAC-adrestabel *	4000 entries	Breedte	209 mm
Store-and-forward	✓	Diepte	126 mm
Packet buffergeheugen	14,88 MB	Hoogte	26 mm
<b>Beveiliging</b>		<b>Verpakking</b>	
IGMP snooping	✓	Snelstartgids	✓
		Gebruikershandleiding	✓
		Breedte verpakking	240 mm
		Diepte verpakking	315 mm

Design		Verpakking	
Kleur van het product	Grijs	Hoogte verpakking	70 mm
Materiaal behuizing	Metaal	Gewicht verpakking	1,24 kg
LED-indicatoren	✓	<b>Logistieke gegevens</b>	
		Code geharmoniseerd systeem (HS) 85176990	



6935364052980



6935364052997

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.