

Zalman ZM700-EBTII power supply unit 700 W 24-pin ATX ATX Zwart

Merk : Zalman

Artikelcode: ZM700-EBTII

Productnaam : ZM700-EBTII

Zalman ZM700-EBTII. Totaal vermogen: 700 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50 - 60 Hz. Motherboard power connector: 24-pin ATX, Lengte stroomkabel moederbord: 60 cm, Lengte SATA-stroomkabel: 600 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 13,5 cm. Breedte: 150 mm, Diepte: 160 mm, Hoogte: 86 mm



Energie		Poorten & interfaces	
Totaal vermogen *	700 W	Lengte PCI Express-stroomkabel	55 cm
AC-ingangsspanning *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC-ingangsfrequentie	50 - 60 Hz	Lengte CPU-stroomkabel	55 cm
Stroom	4.5 - 9 A	ATX Power connector (24-pin)	✓
Power factor	99,9	Floppy drive power connector	1
Power Factor Correctie (PFC) type	Actief	Bekabelingstype	Volledig modulair
Gecombineerd vermogen (+12V)	696 W	Prestatie	
Gecombineerd vermogen (-12V)	3,6 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen(+5Vsb)	15 W	Bedoeld voor *	PC
Max huidige output (+3.3V)	20 A	Vormfactor van de voeding (PSU) *	ATX
Max huidige output(+12V)	58 A	ATX version	2.31
Max huidige output (+5V)	20 A	Stille modus	✓
Max huidige output (-12V)	0,3 A	Bearing technologie	Kogellager
Max huidige output (+5Vsb)	3 A	Mean time between failures (MTBF)	100000 uur
Efficiëntie	91 procent	Certificering	UL, FCC, KC, CE, CB, RoHS, EAC
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting, Onder spanning	Design	
Poorten & interfaces		Kleur van het product	Zwart
Motherboard power connector *	24-pin ATX	Type koeling	Actief
Lengte stroomkabel moederbord	60 cm	Ventilator diameter	13,5 cm
Aantal SATA power connectors	8	Aantal ventilatoren	1 ventilator(en)
Lengte SATA-stroomkabel	600 mm	Ventilator snelheid	1000 - 1900 RPM
Peripheral (Molex) power connectors (4-pin) *	3	Ventilator locatie	Boven
Lengte stroomkabel randapparaat (Molex)	600 mm	Aan/uitschakelaar	✓
EPS power connector (8-pin)	✓	Eisen aan de omgeving	
EPS-voedingsconnector (4+4 pin)	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
PCI Express power connectors (6+2 pin)	5	Gewicht en omvang	
		Breedte	150 mm
		Diepte	160 mm
		Hoogte	86 mm
		Gewicht	3,08 kg



8809213769283

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-SEP-2024. Prints or copies of Information are only valid on the printed Publication date