NETGEAR

NETGEAR Insight Cloud Managed WiFi 6 AX1800 Dual Band Access Point (WAX610)

Merk : NETGEAR

Artikelcode: WAX610-100EUS

Productnaam : Insight Cloud Managed WiFi 6 AX1800 Dual Band Access Point (WAX610)

draadloos access point (WAX610) - WiFi 6 Dual-Band AX1800-snelheid | Tot 200 clientapparaten | 1 x 2,5G Ethernet LAN-poort | 802.11ax | Insight Remote Management | PoE+ | Netvoedingsadapter niet meegeleverd

NETGEAR Insight Cloud Managed WiFi 6 AX1800 Dual Band Access Point (WAX610). 2,4 GHz, 5 GHz, Maximale overdrachtssnelheid van gegevens: 1800 Mbit/s. Ondersteunde beveiligingsalgoritmen: EAP-PEAP, EAP-TLS, EAP-TTLS, PEAP, SSH, SSL/TLS, WPA, WPA2, WPA2-Enterprise, WPA3. Ethernet LAN, dataoverdrachtsnelheden: 10,100,1000,2500 Mbit/s. Power over Ethernet (PoE). Kleur van het product: Wit





| Features | | Power | |
|--|--|---|--|
| 2.4 GHz * 5 GHz * Maximum data transfer rate * | ✓ ✓ 1800 Mbit/s | Power over Ethernet (PoE) * AC input voltage Input current | ✓ 12 V 2.5 A |
| Maximum data transfer rate (2.4 GHz) Maximum data transfer rate (5 GHz) Ethernet LAN data rates Networking standards Number of users Auto MDI/MDI-X MIMO MIMO type Spread spectrum method Wi-Fi Multimedia (WMM)/(WME) | 600 Mbit/s | Design Placement * Product colour * Reset button LED indicators Antenna Antenna type * Antenna gain level (max) Weight & dimensions Width Depth Height Weight | Ceiling, Wall White ✓ LAN, Power, Status Internal 4.5 dBi 160.9 mm 160.9 mm 33.2 mm 412 g |
| VLAN support | ✓ | Packaging data | |
| Security Security algorithms * MAC address filtering Service Set Identifier (SSID) features | EAP-PEAP, EAP-TLS, EAP-TTLS, PEAP, SSH, SSL/TLS, WPA, WPA2, WPA2- Enterprise, WPA3 Multiple SSIDs, SSID broadcast, SSID broadcast on/off | Package width Package depth Package height Package weight Packaging content Quantity per pack | 220 mm 455 mm 235 mm 3.98 kg 1 pc(s) |
| Number of SSID supported Auto Wireless Distribution System (WDS) | 8 | Mounting kit Operational conditions Operating temperature (T-T) | ✔ 0 - 40 °C |

| Security | | Logistics data | |
|--|---|-----------------------------|----------|
| Remote Authentication Dial-In User Service (RADIUS) | 1 | Harmonized System (HS) code | 85176990 |
| Ports & interfaces | | | |
| Ethernet LAN (RJ-45) ports * | 1 | | |
| DC-in jack | 1 | | |











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.